

DIN EN 12952-3:2023-01 (Englisc h)

Water-tube boilers and auxiliary installations - Part 3: Design and calculation for pressure parts of the boiler

Contents		Page
European foreword		8
1	Scope	10
2	Normative references	10
3	Terms and definitions	11
4	Symbols and abbreviations	11
5	General	11
5.1	Purpose	11
5.2	Dimensions of pressure parts	11
5.3	Strength of pressure parts	12
5.4	Design by analysis	12
5.5	Cyclic loading	12
5.6	Other design requirements	13
5.6.1	General	13
5.6.2	Access	14
5.6.3	Drainage and venting	14
5.7	Design, calculation and test pressures	14
5.7.1	Design pressure	14
5.7.2	Calculation pressure	14
5.7.3	Calculation pressure for pressure differences	15
5.7.4	Hydrostatic test	15
5.8	Metal wastage	16
5.8.1	Internal wastage	16
5.8.2	External wastage	16
5.8.3	Requirements	16
5.8.4	Stress corrosion	16
5.8.5	Mechanical requirements	17
5.9	Attachment on pressure parts	17
5.9.1	Load carrying attachments	17
5.9.2	Non load carrying attachments	17
6	Calculation temperature and nominal design stress	17
6.1	Calculation temperature	17
6.1.1	General	17
6.1.2	Circulation boilers	18
6.1.3	Once-through boilers, superheaters and reheaters	18
6.1.4	Hot water generators	18
6.1.5	Temperature allowances for unheated components	18
6.1.6	Headers	19
6.1.7	Unheated components	19
6.1.8	Components protected against radiation	19
6.1.9	Components heated by convection	19
6.1.10	Components heated by radiation	20
6.2	Maximum through-the-wall temperature difference and maximum flue gas temperature for heated drums and headers	21
6.2.1	Maximum through-the-wall temperature difference	21
6.2.2	Headers exposed to flue gas	21

6.2.3	Allowable deviations	22
6.3	Design stress	22
6.3.1	General	22
6.3.2	Rolled and forged steels	23
6.3.3	Austenitic steels	23
6.3.4	Non-alloy and low-alloy cast steel	24
6.3.5	Nodular graphite cast iron	24
6.3.6	Design stress for welded connections operating under creep condition	25
6.3.7	Design stress for test pressure	25
7	Cylindrical shells of drums and headers under internal pressure	25
7.1	Shell thickness	25
7.1.1	Requirements	25
7.1.2	Required wall thickness including allowances	26
7.2	Basic calculation	26
7.2.1	Required wall thickness without allowances	26
7.2.2	Different thickness	26
7.2.3	Fabrication tolerances	26
7.3	Combined stress in drum or header shells	27
7.3.1	General	27
7.3.2	Stress from longitudinal loads	27
7.3.3	Longitudinal bending stress	28
7.3.4	Evaluation of ligament stress for inclined ligaments in drums	29
7.4	Boiler drum supports	30
7.5	Other stresses in cylindrical shells	31
8	Openings and branches in cylindrical shells of drums and headers and integral tubes ...	31
8.1	General	31
8.1.1	Requirements for the ligament efficiency of the main body with openings and branches .	31
8.1.2	Effective lengths for calculation of efficiencies of components	36
8.1.3	Conditions for isolated openings	37
8.1.4	Requirements for design of branches	37
8.1.5	Requirements for the design of reinforcing pads	38
8.2	Efficiency factor, calculation by way of approximation, and maximum diameter of unreinforced openings	38
8.2.1	General	38
8.2.2	Allowable efficiency and maximum diameter of unreinforced opening	38
8.2.3	Isolated openings	39
8.2.4	Adjacent openings	41
8.3	Design of openings and branches in cylindrical shells (efficiency and reinforcement)	42
8.3.1	Symbols and abbreviations	42
8.3.2	Requirements for application	42
8.3.3	Design of isolated openings and branch connections	47
8.3.4	Design of adjacent openings and branch connections	50
8.4	Bolted connections	51
8.4.1	General	51
8.4.2	Symbols and abbreviations	52
8.4.3	Calculation of bolt diameter	53
8.4.4	Calculation of bolt load	54
8.4.5	Calculation temperature t_c	56
8.4.6	Design strength value K	57
8.4.7	Safety factor S	57
8.4.8	Quality factor q	57
8.5	Screwed and socket welded connections	58
8.5.1	Screwed connections into the belt	58
8.5.2	Screwed socket connections	58
8.5.3	Socket welded connections	59
9	Headers and plain tubes of rectangular section	60
9.1	General	60
9.2	Symbols and abbreviations	62
9.3	Required wall thickness	63

9.3.1	General	63
9.3.2	Minimum wall thickness at the centre of one side	64
9.3.3	Minimum wall thickness at the corners	64
9.3.4	Minimum thickness at a line of openings	64
9.3.5	Minimum wall thickness at staggered opening arrangement (diagonal pitch)	65
9.3.6	Minimum wall thickness at isolated openings	65
10	Ends and spherical shells	66
10.1	Symbols and abbreviations	66
10.2	Spherical shells and dished heads	66
10.2.1	General	66
10.2.2	Calculation formula	68
10.2.3	Openings in dished ends and spherical ends	71
10.3	Unstayed flat ends	75
10.3.1	General	75
10.3.2	Thickness of circular unstayed flat ends	78
10.3.3	Thickness of non-circular and rectangular unstayed flat ends	78
10.4	Flat unstayed closures	81
11	Tubes	83
11.1	Symbols and abbreviations	83
11.2	Thickness of straight boiler tubes	83
11.2.1	Required wall thickness with allowances	83
11.2.2	Required wall thickness without allowances	84
11.2.3	Minimum thickness	84
11.2.4	Circumferentially butt welded tubes	85
11.3	Thickness of tube bends and elbows	85
11.3.1	General	85
11.3.2	Required wall thickness with allowances	85
11.3.3	Required wall thickness without allowances	86
11.3.4	Departure from circularity of tube bends	86
11.4	Flexibility of integral tubing systems	87
11.4.1	General	87
11.4.2	Analysis	87
11.5	Structural attachments to tubes	87
11.5.1	General	87
11.5.2	Attachments welded on tube bends	89
11.5.3	Length of attachments	89
11.5.4	Limit of intensity in the case of radial loading	89
11.5.5	Calculation of intensity in the case of radial loading	89
11.5.6	Strength of welds	91
11.6	Fitting and joining of heated tubes	92
11.6.1	Fitting of tubes	92
11.6.2	Joining of heated tubes	92
11.7	Joining of unheated tubes	92
11.7.1	General	92
11.7.2	Flanges and bolting	92
11.7.3	Butt welded joints	92
11.7.4	Screwed or screwed and seal welded joints	92
11.8	Standardized fittings	92
12	Pressure parts of irregular shape	93
12.1	Hydrostatic test for determining the allowable internal pressure	93
12.1.1	General	93
12.1.2	Proof test to produce yielding	93
12.1.3	Proof test to destruction	94
12.2	Numerical methods	94
12.2.1	General	94
12.2.2	Methods	94
12.2.3	Evaluation of stress	95
13	Fatigue	95

13.1	General	95
13.1.1	Procedure	95
13.1.2	Fatigue loading	95
13.1.3	Calculation of fluctuating stress	96
13.1.4	Fatigue assessment	96
13.2	Symbols and abbreviations	96
13.3	Exemption rule for fatigue analysis	98
13.3.1	General	98
13.3.2	Materials	98
13.3.3	Loadings	99
13.3.4	Temperature differences during transient operating conditions	100
13.4	Stress analysis for fatigue calculation	106
13.4.1	Principal and equivalent stresses	106
13.4.2	Temperature of a load cycle	106
13.4.3	Protection of the magnetite layer	107
13.4.4	Allowable circumferential stress range at the inside corner of a bore	107
13.4.5	Circumferential stress caused by pressure at the inside corner of a bore	107
13.4.6	Stresses on the branch caused by external forces and moments	108
13.4.7	Thermal stresses	108
13.4.8	Upper and lower limit of the circumferential stress at the inside corner of a bore	108
13.4.9	Admissible through-the-wall temperature differences	112
13.4.10	Allowable temperature transients	113
13.4.11	Components with oblique and/or non-radial branches	113
13.5	Example calculations	113
Annex A (normative) Calculation of tube bends and elbows		
A.1	General	117
A.2	Symbols and abbreviations	117
A.3	Calculation	118
A.3.1	Required wall thickness	118
A.3.2	Calculation of the wall thickness	118
A.3.3	Calculation of stress	120
A.3.3.1	The strength conditions for the intrados of the bend shall be:	120
A.3.3.2	The strength conditions for the extrados of the bend shall be:	120
Annex B (normative) Fatigue cracking - Design to allow for fluctuating stress		127
B.1	General	127
B.2	Conditions	127
B.3	Symbols and abbreviations	129
B.4	Cyclic stress range and mean cyclic stress in the case of uniaxial and multiaxial fluctuating stress	130
B.4.1	General	130
B.4.2	Uniaxial stress state	130
B.4.3	Multiaxial stress state with principal stress directions constant	130
B.5	Correction factors for taking into account the influences of surface finish and weldments	132
B.6	Controlling stress range	140
B.6.1	General	140
B.6.1.1	Controlling stress range	140
B.6.1.2	Elastic range	140
B.6.1.3	Partly elastic range	140
B.6.1.4	Fully plastic range	140
B.6.2	Correction factor	141
B.7	Permissible stress range with a known number of load cycles	142
Annex C (informative) Examples of calculating the effects of fatigue		143
C.1	General	143

C.2	Calculation of the admissible number of load cycles	143
C.3	Calculation of the admissible temperature gradient	146
Annex D (informative) Physical properties of steels		150
D.1	General	150
D.2	Symbols and abbreviations	150
D.3	Physical properties	150
D.3.1	Density	150
D.3.2	Differential coefficient of linear thermal expansion	150
D.3.3	Heat capacity	151
D.3.4	Thermal diffusivity	151
D.3.5	Poisson's ratio	151
D.4	Physical properties of steels	151
D.4.1	Data sheet (tables)	151
D.4.2	Graphs	153
D.4.3	Polynomials	157
Annex E (informative) Consideration of external wastage due to flue gas exposure		160
E.1	General	160
E.2	Symbols and abbreviations	160
E.3	Wall thickness of straight tubes in accordance to Clause 11	160
E.3.1	Required wall thickness with allowance	160
E.3.2	Required wall thickness without allowances	160
E.3.3	Circumferentially butt welded tubes	160
E.4	Wall thickness of tube bends and elbows in accordance with Clause 11	161
E.4.1	Required wall thickness with allowance	161
E.4.2	Required wall thickness without allowances	161
E.5	Wall thickness of tube bends and elbows in accordance with Annex A	161
Annex F (informative) Significant technical changes between this European Standard and the previous edition		162
Annex ZA (informative) Clauses of this European Standard addressing essential safety requirements of the Pressure Equipment Directive 2014/68/EU		163
Bibliography		165