

# DIN 6647-1:2006-12 (E)

## Means of packaging - Cylindrical beverage containers - Part 1: Allowable operating pressure up to 3 bar, nominal volume up to 50 litres

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>3</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Dimensions and designation .....</b>	<b>4</b>
<b>4</b>	<b>Material .....</b>	<b>6</b>
<b>5</b>	<b>Design .....</b>	<b>6</b>
<b>5.1</b>	<b>General .....</b>	<b>6</b>
<b>5.2</b>	<b>Hygiene .....</b>	<b>6</b>
<b>6</b>	<b>Requirements .....</b>	<b>6</b>
<b>6.1</b>	<b>Constancy of volume .....</b>	<b>6</b>
<b>6.2</b>	<b>Dimensional stability .....</b>	<b>6</b>
<b>6.3</b>	<b>Safety against bursting .....</b>	<b>6</b>
<b>7</b>	<b>Testing .....</b>	<b>7</b>
<b>7.1</b>	<b>General .....</b>	<b>7</b>
<b>7.2</b>	<b>Procedure .....</b>	<b>7</b>
<b>7.3</b>	<b>Constancy of volume .....</b>	<b>7</b>
<b>7.4</b>	<b>Dimensional stability .....</b>	<b>7</b>
<b>7.5</b>	<b>Pressure test .....</b>	<b>8</b>
<b>7.6</b>	<b>Hygiene .....</b>	<b>8</b>
<b>8</b>	<b>Marking .....</b>	<b>8</b>
<b>Annex A (informative)</b>	<b>Bibliography .....</b>	<b>9</b>