

DIN 6847-2:2008-09 (E)

Medical electron accelerators - Part 2: Rules for the construction of structural radiation protection

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and indices	5
3.1	Terms	5
3.2	Indices	7
4	Dose and dose rate information	7
5	Maximum values for the dose behind the shielding	7
6	Room requirements	8
7	Specifications of the MANUFACTURER and of the PERSON RESPONSIBLE FOR RADIATION PROTECTION	8
7.1	Specifications of the MANUFACTURER	8
7.2	Specifications of the PERSON RESPONSIBLE FOR RADIATION PROTECTION	10
8	Operating data	10
8.1	RADIATION ENERGY	10
8.2	Dose rate	10
8.3	WORKING LOAD	11
8.4	DIRECTION FACTOR	11
8.5	OCCUPATION FACTOR	12
8.6	Interaction of factors U and T	12
9	Maximum permissible AREA DOSE	13
10	Rating of radioprotective shielding	13
10.1	General	13
10.2	General calculation scheme	14
10.3	Shielding against BREMSSTRAHLUNG in useful radiation direction	14
10.4	Shielding against electron useful radiation	15
10.5	Shielding against LEAKAGE RADIATION	16
10.6	Shielding against secondary BREMSSTRAHLUNG	19
10.7	Shielding against tertiary BREMSSTRAHLUNG	21
10.8	Shielding against NEUTRON RADIATION	22
10.9	Interaction of several radiation sources, types and components	26
10.10	Structural radiation protection measures against RADIOACTIVE MATERIAL created by nuclear photoprocesses	27
11	Constructional radiation protection drawing	28
11.1	Specifications of the installer	28
11.2	Safekeeping of the as-built radiation protection drawing	28
12	Check for compliance with radiation protection rules	28
12.1	Requirements placed on the rooms in accordance with 6 d) to 6 i)	28
12.2	Check of the structural shieldings which may be hit by the USEFUL BEAM	28

12.3	Check of the structural shieldings which cannot be hit by the USEFUL BEAM	29
13	Test of VENTILATION SYSTEM	29
	Annex A (informative) Calculation example	31
	Bibliography	37
	Index of defined terms	38
Figures	Figure 1 -- Product of the THICKNESS AT TENTH MAXIMUM zX and density for BREMSSTRAHLUNG, LEAKAGE RADIATION, X-ray radiation share in the USEFUL BEAM of the ELECTRON RADIATION and BREMSSTRAHLUNG in the useful radiation direction generated by electrons outside the RADIATION SOURCE ASSEMBLY, for the materials specified in the key	17
	Figure 2 -- Product of the THICKNESS AT TENTH MAXIMUM zX and density for BREMSSTRAHLUNG, LEAKAGE RADIATION, X-ray radiation share in the USEFUL BEAM of the ELECTRON RADIATION and BREMSSTRAHLUNG in the useful radiation direction generated by electrons outside the RADIATION SOURCE ASSEMBLY, for the materials specified in the key	18
	Figure 3 -- Factor kXE for calculation of shieldings against BREMSSTRAHLUNG in useful radiation direction generated outside of the RADIATION SOURCE ASSEMBLY	19
	Figure A.1 -- Floor plan view for the rating of radioprotective shielding in ELECTRON ACCELERATOR INSTALLATIONS	32
Tables	Table 1 -- Maximum permissible AREA DOSE HW	13
	Table 2 -- Product of THICKNESS AT TENTH MAXIMUM zXs or zXt and density r for secondary or tertiary BREMSSTRAHLUNG	20
	Table 3 -- THICKNESS AT TENTH MAXIMUM zNn and zNs for NEUTRON RADIATION	24
	Table 4 -- Parameters for rating radioprotective shielding according to 10.2 to 10.8	25
	Table 5 -- Reinforcing shieldings for the interaction of several radiation components	27
	Table A.1 -- Radiation conditions according to specifications of the PERSON RESPONSIBLE FOR RADIATION PROTECTION for the calculation example to rate the radioprotective shielding according to Figure A.1	33
	Table A.2 -- Operating data according to specifications of the MANUFACTURER for the calculation example to rate the radioprotective shielding according to Figure A.1	34
	Table A.3 -- Calculation data to rate the radioprotective shielding for the various different radiation components and occupied areas in the calculation example according to Figure A.1	35