

DIN 6847-2:2021-06 (E)

Medical electron accelerators - Part 2: Structural requirements for radiation protection and requirements for testing of approval conditions for operation

Contents		Page
Foreword		5
1	Scope	7
2	Normative references	7
3	Terms and definitions and indices	7
3.1	Terms and definitions	8
3.2	Indices	10
4	Dose and dose rate information	11
5	Maximum values for the dose behind the shielding	11
6	Room requirements	11
7	Specifications of the manufacturer and of the radiation protection responsible person	12
7.1	Specifications of the manufacturer	12
7.2	Specifications of the radiation protection responsible person	13
8	Operational data	14
8.1	Radiation energy	14
8.2	Dose rate	14
8.3	Working load WA	14
8.4	Direction factor	15
8.5	Occupation factor	16
8.6	Interaction of factors U and T	16
9	Maximum permissible area dose	17
10	Rating of radioprotective shielding	17
10.1	General	17
10.2	General calculation scheme	18
10.3	Shielding against bremsstrahlung in the useful radiation direction	19
10.4	Shielding against electron useful radiation	20
10.5	Shielding against leakage radiation	21
10.6	Shielding against secondary bremsstrahlung	25
10.7	Shielding at the access to the irradiation room	28
10.7.1	Shielding at the radiation protection labyrinth	28
10.7.2	Shielding at the gate of an irradiation room without a radiation protection labyrinth	29
10.8	Shielding against neutron radiation	30
10.9	Shielding the radiation protection labyrinth	35
10.10	Interaction of several radiation sources and components	37
10.11	Structural radiation protection measures against radioactive material created by nuclear photoprocesses	38
11	Constructional radiation protection drawing	38
11.1	Specifications of the constructor	38
11.2	Safekeeping of the radiation protection drawing	39
12	Check for compliance with radiation protection rules	39

12.1	General	39
12.2	Check of requirements placed on the rooms in accordance with 6 c) to 6 i)	39
12.3	Check of the structural shielding	39
12.3.1	General	39
12.3.2	Requirements on the measuring equipment	39
12.3.3	Checking the requirements for the structural shielding	40
12.3.4	Evaluation of measured results	41
13	Test of ventilation system	41
Annex A (informative) Tables for the attenuation curves in Figure 3, Figure 4 and Figure 5		42
Annex B (informative) Calculation example		45
Bibliography		52
Index of defined terms		53
Figures Figure 1 -- Example of the distance a_n for useful radiation		19
Figure 2 -- Example of the distance a_n for leakage radiation		22
Figure 3 -- Product of the thickness at tenth maximum z_X and density for bremsstrahlung, leakage radiation, X-ray radiation share in the radiation field of the electron radiation, and bremsstrahlung in the useful radiation direction generated by electrons outside the radiation head, for the materials specified in the key		23
Figure 4 -- Product of the thickness at tenth maximum z_X and density for bremsstrahlung, leakage radiation, X-ray radiation share in the radiation field of the electron radiation, and bremsstrahlung in the useful radiation direction generated by electrons outside the radiation head, for the materials specified in the key		24
Figure 5 -- Factor k_{XE} for calculation of shielding against bremsstrahlung in useful radiation direction generated outside of the radiation head		25
Figure 6 -- Example of the distance a_{Xs} for secondary bremsstrahlung		27
Figure 7 -- Example of the distance a_{Xt} and surface AX_t for tertiary bremsstrahlung		29
Figure 8-- Example of the distance a_{Nn} for direct neutron radiation		31
Figure 9 -- Example of distance a_{Ns} for scattered neutron radiation		33
Figure 10 -- Labyrinth length and width (schematic)		34
Figure B.1 -- Floor plan view for the rating of radioprotective shielding in electron accelerator installations (calculation example)		46
Tables Table 1-- Maximum permissible area dose HW		17
Table 2 -- Product of thickness at tenth maximum z_Xs or z_{Xt} and density for secondary or tertiary bremsstrahlung		26
Table 3 -- Thicknesses at tenth maximum z_{Nn} and z_{Ns} for neutron radiation		33
Table 4 -- Parameters for rating radioprotective shielding according to 10.2 to 10.9		35
Table 5 -- Reinforcing shielding against the interaction of several radiation components		38
Table A.1 -- Product of the thickness at tenth maximum z_X and density for bremsstrahlung, leakage radiation, X-ray radiation share in the radiation field of the electron radiation, and bremsstrahlung in the useful radiation direction generated by electrons outside the radiation head, for the materials listed (see Figure 3)		42

Table A.2 -- Product of the thickness at tenth maximum zX and density for bremsstrahlung, leakage radiation, X-ray radiation share in the radiation field of the electron radiation, and bremsstrahlung in the useful radiation direction generated by electrons outside the radiation head, for the materials listed (see Figure 4)	43
Table A.3 -- Factor k_{XE} for calculation of shielding against bremsstrahlung in useful radiation direction generated outside of the radiation head (see Figure 5)	44
Table B.1 -- Radiation conditions according to specifications of the radiation protection responsible person for the calculation example to rate the radioprotective shielding according to Figure B.1	47
Table B.2 -- Operating data according to specifications of the manufacturer for the calculation example to rate the radioprotective shielding according to Figure B.1	48
Table B.3 -- Calculation data to rate the radioprotective shielding for the various radiation components and occupied areas in the calculation example according to Figure B.1	49