

DIN EN 1254-6:2012-12 (E)

Copper and copper alloys - Plumbing fittings - Part 6: Fittings with push-fit ends

Contents	Page
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	8
3 Terms and definitions	9
4 Requirements	10
4.1 General	10
4.2 Materials	10
4.2.1 General	10
4.2.2 Reaction to fire	11
4.2.3 Resistance to high temperature (for heating networks)	11
4.3 Dimensions and tolerances	12
4.3.1 Minimum bore area	12
4.3.2 Minimum bore area through fittings with an integral or separate internal support	12
4.3.3 Tolerance for the alignment of the fitting ends	14
4.4 Design and manufacture	14
4.4.1 Tube and pipe abutment	14
4.4.2 Surface condition	14
4.4.3 Plated or coated surfaces	14
5 Testing, assessment and sampling methods	14
5.1 Type testing	14
5.1.1 General	14
5.1.2 Preparation of fittings for testing	15
5.1.3 Test temperature	15
5.1.4 Leaktightness under internal hydrostatic pressure	15
5.1.5 Resistance to pull-out	16
5.1.6 Temperature cycling	16
5.1.7 Pressure cycling test	17
5.1.8 Vacuum test	18
5.1.9 Vibration test (metallic tube only)	18
5.1.10 Leaktightness under internal hydrostatic pressure while subjected to bending (metallic tube only)	18
5.1.11 Static bending test (plastics pipe only)	19
5.1.12 Disconnection and re-use (for fittings capable of being disconnected)	19
5.1.13 Rotation test	20
5.1.14 Resistance to stress corrosion	20
5.2 Factory production control system	20
5.2.1 General	20
5.2.2 Integrity of fittings bodies with as-cast microstructure or fabricated by welding or brazing	21
5.2.3 Resistance to dezincification	21
6 Evaluation of conformity	21
6.1 General	21
6.2 Type testing	21
6.2.1 General	21

6.2.2	Requirements and characteristics	22
6.2.3	Use of historical data	22
6.2.4	Further type testing	22
6.3	Sampling, testing and conformity criteria	22
6.3.1	Sampling	22
6.3.2	Testing and conformity criteria	22
6.4	Factory production control (FPC)	22
6.4.1	General	22
6.4.2	Personnel	23
6.4.3	Equipment	23
6.4.4	Raw materials and components	23
6.4.5	In-process control	23
6.4.6	Traceability and marking	23
6.4.7	Non-conforming products	23
6.4.8	Corrective action	24
6.4.9	Handling, storage, packaging	24
7	Classification and designation	24
8	Marking	24
8.1	General	24
8.2	Dezincification resistant copper-zinc alloys	25
9	Documentation	25
9.1	Declaration of conformity	25
9.2	User instructions	25
Annex A (normative) Method for testing leaktightness of joints under internal hydrostatic pressure		26
A.1	Introduction	26
A.2	Principle	26
A.3	Apparatus	26
A.4	Test piece	26
A.5	Procedure	27
Annex B (normative) Method for testing resistance to pull-out of joints with metallic tube		28
B.1	Introduction	28
B.2	Principle	28
B.3	Apparatus	28
B.4	Test assembly	28
B.5	Procedure	28
Annex C (normative) Test method for resistance of joints with metallic tube to temperature cycling		30
C.1	Introduction	30
C.2	Principle	30
C.3	Apparatus	30
C.4	Test assembly	30
C.5	Procedure	31
Annex D (normative) Method for testing the resistance of joints with metallic tube to pressure cycling		32
D.1	Introduction	32
D.2	Principle	32
D.3	Apparatus	32
D.4	Test pieces	33
D.5	Procedure	33
Annex E (normative) Test method for leaktightness of joints with metallic tube under vacuum		34

E.1	Introduction	34
E.2	Principle	34
E.3	Apparatus	34
E.4	Test piece	35
E.5	Procedure	35
Annex F (normative) Test method for the resistance of joints with metallic tube to vibration		36
F.1	Introduction	36
F.2	Principle	36
F.3	Apparatus	36
F.4	Test assembly	36
F.5	Procedure	37
Annex G (normative) Test method for leaktightness of joints with metallic tube under internal hydrostatic pressure while subjected to bending		38
G.1	Introduction	38
G.2	Principle	38
G.3	Apparatus	38
G.4	Test piece	38
G.5	Procedure	39
Annex H (normative) Test method for disconnection and re-use		40
H.1	Introduction	40
H.2	Principle	40
H.3	Apparatus	40
H.4	Test assembly	40
H.5	Procedure	40
Annex I (normative) Fitting rotation test		41
I.1	Introduction	41
I.2	Principle	41
I.3	Apparatus	41
I.4	Test assembly	41
I.5	Procedure	42
Annex J (normative) Determination of resistance to stress corrosion		43
J.1	Introduction	43
J.2	Test piece	43
J.3	Procedure	43
J.4	Test report	43
Annex K (normative) Pressure test for fittings bodies with as-cast microstructure or fabricated by welding or brazing		44
K.1	Introduction	44
K.2	Principle	44
K.3	Apparatus	44
K.4	Test piece	44
K.5	Procedure	45
Annex L (normative) Determination of mean depth of dezincification		46
L.1	Introduction	46
L.2	Procedure	46
L.3	Expression of results	46
Bibliography		48