

DIN EN 12953-3:2016-12 (E)

Shell boilers - Part 3: Design and calculation for pressure parts

Contents	Page
European foreword	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviations	8
5 General	8
5.1 Boilers	8
5.2 Hot-water boilers	8
5.3 Main welds	8
5.4 Weld factor	9
5.5 Thermal design of furnaces tubes	9
5.5.1 Design conditions	9
5.5.2 Furnace dimensions	11
5.5.3 Heat input	11
5.5.4 Additional operating conditions	12
5.6 Dimensions of pressure parts	12
5.7 Determination of pressures	12
5.7.1 Maximum allowable pressure	12
5.7.2 Calculation pressure	12
5.7.3 Safety valves set pressure	12
5.7.4 Hydrostatic test pressure	13
5.8 Allowances	13
5.8.1 Allowance for material supply tolerances and forming processes	13
5.8.2 Allowance for metal wastage	13
5.9 Additional material requirements for plates	13
5.10 Standardized fittings	14
5.11 Flanges	14
5.12 Design by analysis	14
5.13 Economizer and superheater	14
6 Calculation temperature and nominal design stress	14
6.1 Calculation temperature	14
6.2 Nominal design stress	15
7 Cylindrical shells	15
7.1 Shell thickness	15
7.1.1 Requirements	15
7.1.2 Required wall thickness including allowances	16
7.2 Basic calculation subjected to internal pressure	16
7.3 Boiler supports and lifting lugs	16
8 Openings and branches in cylindrical shells	16
8.1 General	16
8.1.1 Introduction	16
8.1.2 Requirements for the reinforcement of openings in shells	16
8.1.3 Effective lengths l_{rs} for calculation of efficiencies and of compensations	18
8.1.4 Condition of isolated openings	22

8.1.5	Requirements for design of branches	22
8.1.6	Requirements for design of reinforcing pads	22
8.1.7	General requirements for calculation of cross-sectional and pressure-loaded areas	23
8.2	Efficiency factor, alternative calculation method, maximum diameter of an un-reinforced opening	23
8.2.1	General	23
8.2.2	Allowable efficiency and maximum diameter of an unreinforced opening	24
8.2.3	Isolated openings	24
8.2.4	Adjacent openings	25
8.3	Design of openings and branches in shells (efficiency and reinforcement)	25
8.3.1	Symbols and abbreviations	25
8.3.2	Requirements for application	26
8.3.3	Design of isolated openings and branch connections	30
8.3.4	Design of adjacent openings and branch connections	32
9	Ends	33
9.1	Unstayed dished heads without openings	33
9.1.1	Unstayed dished heads under internal pressure	33
9.1.2	Limiting conditions	33
9.1.3	Unstayed dished heads under external pressure	35
9.2	Flat unstayed removable closures	36
9.3	Unstayed flat plates	37
10	Supported flat plates, stays and stiffeners	38
10.1	Breathing space for flat plates	38
10.2	Stayed flat surfaces	40
10.2.1	General	40
10.2.2	Radius of flange	40
10.2.3	Point of support	40
10.2.4	Thickness	41
10.2.5	Values of constant C4	44
10.2.6	Stays for wet back reversal chambers	54
10.2.7	Stay tubes and bars	56
10.2.8	Loads on stay tubes and bar stays	56
10.2.9	Gusset stays	56
10.2.10	Weld attachments	58
10.2.11	Additional requirements for set-in end plates	58
10.2.12	Girder stays supporting the flat section of a reversal chamber	60
11	Design of isolated openings in boiler flat end plates	60
11.1	Unreinforced isolated openings	60
11.2	Branch openings	60
11.3	Manholes, headholes and handholes	62
12	Unpierced tubes and tube plates	63
12.1	Thickness of straight tubes subject to external pressure	63
12.2	Thickness of straight tubes subject to internal pressure	64
12.3	Wall thickness and ovality of elbows and tube bends	64
12.3.1	General	64
12.3.2	Departure from circularity of the tube bends	64
12.4	Smoke tubes	66
12.5	Pitch of tubes	70
12.6	Thickness of the tube plates within tube nests	70
13	Furnaces tubes, furnace components and reversal chambers of cylindrical form subject to external pressure	71
13.1	Furnaces tubes	71
13.1.1	Plain furnaces tubes	71
13.1.2	Corrugated furnaces tubes	71
13.1.3	Safety factors	72
13.1.4	Furnace components	72
13.1.5	Reversal chambers	72

13.2	Calculation length of composite furnaces tubes	73
13.3	Tolerances of furnaces tubes	74
13.4	Stiffeners	74
13.4.1	General	74
13.4.2	Stiffener sections made from bar or plate	75
13.4.3	Stiffeners located within the zone of peak heat flux	75
13.4.4	Bowling hoops	75
14	Access and inspection openings	78
14.1	General requirements	78
14.2	Types and minimum dimensions of access and inspection openings	79
14.3	Minimum gasket bearing width and clearance for access and inspection doors	81
14.4	Access and inspection openings in flat plates	81
14.5	Requirements for entry area into boilers with a shell outside diameter greater than 1 400 mm	81
14.6	Accessibility and arrangement of entry and inspection openings	81
Annex A (informative) Calculation form for "Walker"-type reverse curve sections or corrugations ..		82
Annex B (normative) Furnace calculation temperature		84
B.1	Calculation of the maximum and the middle furnace wall temperature	84
Annex C (informative) Calculation of tube plate temperatures		87
C.1	General	87
C.2	Symbols	87
C.3	Calculation method	88
C.3.1	Radiation coefficients	88
C.3.2	Convection coefficients	92
C.3.3	Weighted average gas-side heat transfer coefficient	95
C.3.4	Tube plate thermal conductance	97
C.3.5	Water side heat transfer	98
C.3.6	Tube plate temperatures	98
C.4	Example of a calculation carried out using the method given in C.3	101
C.4.1	Design data assumed	101
C.4.2	Calculation of radiation coefficient	102
C.4.3	Calculation of convection coefficients	102
C.4.4	Calculation of weighted average gas-side heat transfer coefficient	102
C.4.5	Calculation of tube plate thermal conductance	102
C.4.6	Calculation of tube plate temperatures	103
Annex D (normative) Economizer and superheater with water tube design connected to the shell boiler		104
D.1	General	104
D.2	Design of economizer and superheater connected to shell boilers	104
Annex E (informative) Significant technical changes between this European Standard and the previous edition		106
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2014/68/EU aimed to be covered		107
Bibliography		108