

ISO 8434-1:2018 (E)

Metallic tube connections for fluid power and general use — Part 1: 24° cone connectors

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Materials
4.1	General
4.2	Connector bodies
4.3	Nuts
4.4	Cutting rings
4.5	O-rings
5	Pressure/temperature requirements
6	Designation of connectors
7	Requirements for tubes
8	Across#flats dimensions and tolerances
9	Design
9.1	Connectors
9.2	Dimensions
9.3	Passage tolerances
9.4	Angular tolerances
9.5	Contour details
9.6	Ports and stud ends
9.7	Stud end sealing
10	Screw threads
10.1	Cone ends and nuts
10.2	Stud ends (connection ends)
11	Manufacture
11.1	Construction
11.2	Workmanship
11.3	Finish
11.4	Corners
12	Assembly instruction
13	Procurement information
14	Marking of components
15	Performance and qualification test
15.1	General
15.2	Repeated assembly test

- 15.3 Proof test
- 15.4 Burst pressure test
- 15.5 Cyclic endurance (impulse) test
- 15.6 Vibration test
- 15.7 Leakage (gas) test
- 15.8 Overtightening test
- 15.8.1 Connectors with cutting rings
- 15.8.2 Connectors with O#ring seal cone (DKO)
- 15.9 Vacuum test
- 16 Identification statement (reference to this document)
- Annex A (normative) Assembly instructions for 24° cone connectors using cutting ring conforming to ISO 8434-1
 - A.1 Cutting ring direct assembly into coupling body
 - A.2 Cutting ring pre-assembly using a manual pre-assembly adapter for final assembly in the connector body

Page count: 52