

ISO 14347:2008-12 (E)

Fatigue - Design procedure for welded hollow-section joints - Recommendations

Contents

	Page
Foreword	iv
1 Scope	1
1.1 General	1
1.2 Materials	1
1.3 Types of joints	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	7
5 Cumulative fatigue damage	12
6 Partial safety factor	12
7 Fatigue design procedures	12
7.1 Hot-spot stress method	12
7.2 Design procedures	13
8 Fatigue strength	13
8.1 Member forces	13
8.2 Nominal stress ranges	14
8.3 SCF calculations	14
8.4 Hot-spot stress ranges	14
8.5 Fatigue strength curves	15
9 SCF calculations for CHS joints	17
9.1 Uniplanar CHS T- and Y-joints	17
9.2 Uniplanar CHS X-joints	18
9.3 Uniplanar CHS K-joints with gap	18
9.4 Multiplanar CHS XX-joints	19
9.5 Multiplanar CHS KK-joints with gap	20
9.6 Minimum SCF values	21
10 SCF calculations for RHS joints	21
10.1 Uniplanar RHS T- and X-joints	21
10.2 Uniplanar RHS K-joints with gap	22
10.3 Uniplanar RHS K-joints with overlap	23
10.4 Multiplanar RHS KK-joints with gap	24
10.5 Minimum SCF values	25
Annex A (normative) Quality requirements for hollow sections	26
Annex B (normative) Weld details	27
Annex C (informative) A fatigue assessment procedure	29
Annex D (normative) SCF equations and graphs for CHS joints	31
Annex E (normative) SCF equations and graphs for RHS joints	47
Bibliography	67