

# ISO/TR 26946:2011-11 (E)

## Standard method for porosity measurement of thermally sprayed coatings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Purpose .....</b>	<b>1</b>
<b>3</b>	<b>Classification .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>1</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>6</b>	<b>Metallographic preparation .....</b>	<b>2</b>
<b>6.1</b>	<b>General .....</b>	<b>2</b>
<b>6.2</b>	<b>Sectioning .....</b>	<b>2</b>
<b>6.3</b>	<b>Cleaning .....</b>	<b>2</b>
<b>6.4</b>	<b>Mounting .....</b>	<b>3</b>
<b>6.5</b>	<b>Grinding and polishing .....</b>	<b>3</b>
<b>7</b>	<b>Metallography procedure .....</b>	<b>5</b>
<b>8</b>	<b>Presentation of porosity .....</b>	<b>6</b>
<b>9</b>	<b>Test report .....</b>	<b>6</b>
<b>Annex A (informative) List of t values with different n and values .....</b>		<b>8</b>
<b>Annex B (informative) Report of an international round robin test on the determination of porosity in plasma sprayed ceramic coatings by using image analysis of metallographically prepared cross sections .....</b>		<b>9</b>
<b>B.1</b>	<b>Introduction .....</b>	<b>9</b>
<b>B.2</b>	<b>Scheme of the round robin test .....</b>	<b>9</b>
<b>B.2.1</b>	<b>Participants .....</b>	<b>9</b>
<b>B.2.2</b>	<b>Sample preparation .....</b>	<b>9</b>
<b>B.2.3</b>	<b>Guideline of procedures for porosity measurement .....</b>	<b>10</b>
<b>B.3</b>	<b>Results and discussion .....</b>	<b>11</b>
<b>B.3.1</b>	<b>Initial results .....</b>	<b>11</b>
<b>B.3.2</b>	<b>Second round test carried out in Japan .....</b>	<b>12</b>
<b>B.4</b>	<b>Reassessment of the round robin tests by the grinding/polishing conditions .....</b>	<b>15</b>
<b>B.5</b>	<b>SEM imaging mode .....</b>	<b>19</b>
<b>B.6</b>	<b>Summary .....</b>	<b>19</b>