ISO 14113:2013-10 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 MPa)

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Construction 3
4.1 Hose 3
4.2 End fittings 3
4.3 Hose assemblies 3

5 Dimensions and tolerances 3
5.1 Bore size 3
5.2 Concentricity 3
5.3 Cut lengths and tolerances 4
5.4 Length of hoses assemblies 4

6 Physical properties of lining and cover -- Type tests 4
6.1 General 4
6.2 Resistance to ignition requirement for oxygen hose lining 5
6.3 Resistance to acetone (acetylene hose only) 5

7 Performance requirements -- Type tests 5
7.1 Pressure resistance requirements 5
7.2 Adhesion (rubber hoses only) 6
7.3 Flexibility 6
7.4 Low temperature flexibility 6
7.5 Ozone resistance (for hoses with an outer protective cover of rubber) 6
7.6 UV resistance (for hoses with plastics cover) 6
7.7 Permeability to gas 6
7.8 Electrical conductivity 6
7.9 End fitting integrity 6

8 Performance requirements -- Production tests 7
8.1 Pressure tests for hose assemblies 7
8.2 Leak test 7
8.3 Cleaning for oxygen service 7

9 Marking 7

10 Packaging 8

11 Instructions 8

Annex A (normative) Acetylene decomposition test for hose assemblies used in high pressure acetylene installations 9

Annex B (normative) Oxygen pressure surge test 10

Annex C (normative) Oxygen system installation considerations 12

Bibliography 13