

ISO 14113:2013-10 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 MPa)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Construction	3
4.1	Hose	3
4.2	End fittings	3
4.3	Hose assemblies	3
5	Dimensions and tolerances	3
5.1	Bore size	3
5.2	Concentricity	3
5.3	Cut lengths and tolerances	4
5.4	Length of hoses assemblies	4
6	Physical properties of lining and cover -- Type tests	4
6.1	General	4
6.2	Resistance to ignition requirement for oxygen hose lining	5
6.3	Resistance to acetone (acetylene hose only)	5
7	Performance requirements -- Type tests	5
7.1	Pressure resistance requirements	5
7.2	Adhesion (rubber hoses only)	6
7.3	Flexibility	6
7.4	Low temperature flexibility	6
7.5	Ozone resistance (for hoses with an outer protective cover of rubber)	6
7.6	UV resistance (for hoses with plastics cover)	6
7.7	Permeability to gas	6
7.8	Electrical conductivity	6
7.9	End fitting integrity	6
8	Performance requirements -- Production tests	7
8.1	Pressure tests for hose assemblies	7
8.2	Leak test	7
8.3	Cleaning for oxygen service	7
9	Marking	7
10	Packaging	8
11	Instructions	8
Annex A (normative)	Acetylene decomposition test for hose assemblies used in high pressure acetylene installations	9
Annex B (normative)	Oxygen pressure surge test	10

Annex C (normative) Oxygen system installation considerations	12
Bibliography	13