

ISO 14113:2013-10 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 MPa)

| Contents | | Page |
|----------------------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Construction | 3 |
| 4.1 | Hose | 3 |
| 4.2 | End fittings | 3 |
| 4.3 | Hose assemblies | 3 |
| 5 | Dimensions and tolerances | 3 |
| 5.1 | Bore size | 3 |
| 5.2 | Concentricity | 3 |
| 5.3 | Cut lengths and tolerances | 4 |
| 5.4 | Length of hoses assemblies | 4 |
| 6 | Physical properties of lining and cover -- Type tests | 4 |
| 6.1 | General | 4 |
| 6.2 | Resistance to ignition requirement for oxygen hose lining | 5 |
| 6.3 | Resistance to acetone (acetylene hose only) | 5 |
| 7 | Performance requirements -- Type tests | 5 |
| 7.1 | Pressure resistance requirements | 5 |
| 7.2 | Adhesion (rubber hoses only) | 6 |
| 7.3 | Flexibility | 6 |
| 7.4 | Low temperature flexibility | 6 |
| 7.5 | Ozone resistance (for hoses with an outer protective cover of rubber) | 6 |
| 7.6 | UV resistance (for hoses with plastics cover) | 6 |
| 7.7 | Permeability to gas | 6 |
| 7.8 | Electrical conductivity | 6 |
| 7.9 | End fitting integrity | 6 |
| 8 | Performance requirements -- Production tests | 7 |
| 8.1 | Pressure tests for hose assemblies | 7 |
| 8.2 | Leak test | 7 |
| 8.3 | Cleaning for oxygen service | 7 |
| 9 | Marking | 7 |
| 10 | Packaging | 8 |
| 11 | Instructions | 8 |
| Annex A (normative) | Acetylene decomposition test for hose assemblies used in high pressure acetylene installations | 9 |
| Annex B (normative) | Oxygen pressure surge test | 10 |

| | |
|--|-----------|
| Annex C (normative) Oxygen system installation considerations | 12 |
| Bibliography | 13 |