DIN EN ISO 14113:2014-02 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 M Pa) (ISO 14113:2013)

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Termsanddefinitions 5

4 Construction 6
4.1 Hose 6
4.2 End fittings 6
4.3 Hose assemblies 6

5 Dimensions and tolerances 6
5.1 Bore size 6
5.2 Concentricity 6
5.3 Cut lengths and tolerances 7
5.4 Length of hoses assemblies 7

6 Physical properties of lining and cover -- Type tests 7
6.1 General 7
6.2 Resistance to ignition requirement for oxygen hose lining 8
6.3 Resistance to acetone (acetylene hose only) 8

7 Performance requirements -- Type tests 8
7.1 Pressure resistance requirements 8
7.2 Adhesion (rubber hoses only) 9
7.3 Flexibility 9
7.4 Low temperature flexibility 9
7.5 Ozone resistance (for hoses with an outer protective cover of rubber) 9
7.6 UV resistance (for hoses with plastics cover) 9
7.7 Permeability to gas 9
7.8 Electrical conductivity 9
7.9 End fitting integrity 9

8 Performance requirements -- Production tests 10
8.1 Pressure tests for hose assemblies 10
8.2 Leak test 10
8.3 Cleaning for oxygen service 10

9 Marking 10

10 Packaging 11

11 Instructions 11

Annex A (normative) Acetylene decomposition test for hose assemblies used in high pressure acetylene installations 12

Annex B (normative) Oxygen pressure surge test 13

Annex C (normative) Oxygen system installation considerations 15

Bibliography 16