

DIN EN ISO 14113:2014-02 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 M Pa) (ISO 14113:2013)

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 Construction	6
4.1 Hose	6
4.2 End fittings	6
4.3 Hose assemblies	6
5 Dimensions and tolerances	6
5.1 Bore size	6
5.2 Concentricity	6
5.3 Cut lengths and tolerances	7
5.4 Length of hoses assemblies	7
6 Physical properties of lining and cover -- Type tests	7
6.1 General	7
6.2 Resistance to ignition requirement for oxygen hose lining	8
6.3 Resistance to acetone (acetylene hose only)	8
7 Performance requirements -- Type tests	8
7.1 Pressure resistance requirements	8
7.2 Adhesion (rubber hoses only)	9
7.3 Flexibility	9
7.4 Low temperature flexibility	9
7.5 Ozone resistance (for hoses with an outer protective cover of rubber)	9
7.6 UV resistance (for hoses with plastics cover)	9
7.7 Permeability to gas	9
7.8 Electrical conductivity	9
7.9 End fitting integrity	9
8 Performance requirements -- Production tests	10
8.1 Pressure tests for hose assemblies	10
8.2 Leak test	10
8.3 Cleaning for oxygen service	10
9 Marking	10
10 Packaging	11
11 Instructions	11
Annex A (normative) Acetylene decomposition test for hose assemblies used in high pressure acetylene installations	12
Annex B (normative) Oxygen pressure surge test	13

Annex C (normative) Oxygen system installation considerations	15
Bibliography	16