

DIN EN 16813:2017-02 (E)

Thermal spraying - Measurement of the electrical conductivity of thermal sprayed non-iron metal coatings by means of eddy current method

| Contents | | Page |
|--|---|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Measuring process | 6 |
| 4.1 | Measuring method | 6 |
| 4.2 | Calibration standard | 7 |
| 4.3 | Measuring frequency and penetration depth | 8 |
| 4.4 | Measuring instruments | 8 |
| 4.5 | Factors, which have effects on the uncertainty of the measurement | 9 |
| 4.6 | Limit of application | 9 |
| 5 | Procedure of the measurement | 10 |
| 5.1 | Calibration of the measuring instruments | 10 |
| 5.2 | Measurement | 10 |
| 6 | Measuring results and their assessment | 10 |
| 7 | Test report and documentation | 11 |
| Annex A (informative) Record for the applied Electrical Conductivity Measurement | | 12 |
| A.1 | General | 12 |
| A.2 | Component/part | 12 |
| A.3 | Surface preparation for spraying | 12 |
| A.4 | Spraying procedure for component/part | 12 |
| A.5 | Preparation of measurement | 13 |
| A.6 | Measuring instrument | 13 |
| A.7 | Result of the measured electrical conductivity | 13 |
| Bibliography | | 14 |