

# DIN EN 1395-5:2018-10 (E)

## Thermal spraying - Acceptance inspection of thermal spraying equipment - Part 5: Plasma spraying in chambers

---

| <b>Contents</b>  | <b>Page</b> |
|--|-------------|
| European foreword .....  | 3           |
| 1 Scope .....  | 4           |
| 2 Normative references .....   | 4           |
| 3 Terms and definitions .....  | 4           |
| 4 Principles of acceptance inspection .....  | 5           |
| 4.1 General .....  | 5           |
| 4.2 Typical components .....   | 5           |
| 5 Procedure for acceptance inspection of vacuum components .....   | 5           |
| 5.1 General .....  | 5           |
| 5.2 Low pressure performance of the pump station .....   | 6           |
| 5.3 Low pressure performance of the chamber .....  | 6           |
| 5.3.1 Preparation .....  | 6           |
| 5.3.2 Determination of the leakage rate ( $Q_L$ ) .....  | 6           |
| 5.3.3 Assessment of leakage rate .....   | 7           |
| 5.4 Function test .....  | 7           |
| 6 Designation .....  | 8           |
| 7 Inspection report .....  | 8           |
| Annex A (informative) Inspection report for chamber and pump systems for plasma spraying<br>in controlled atmosphere (initial test/retest) .....               | 9           |
| Annex B (informative) Diagram for the chronological sequence of the pressure change in<br>chamber and an example for the calculation of the leakage rate ..... | 11          |
| B.1 Diagram .....  | 11          |
| B.2 Example for the calculation .....  | 12          |
| Bibliography .....   | 13          |
| <br>   |             |
| <b>Figures</b>   |             |
| Figure B.1 - Typical graph of pressure as function of time .....   | 11          |