ISO 9455-16:2019 (E)

Soft soldering fluxes — Test methods — Part 16: Flux efficacy test, wetting balance method

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Principle

6 Reagents

7 Apparatus

8 Test pieces

9 Procedure

- 9.1 Preparation of the test pieces
- 9.1.1 Cleaning
- 9.1.2 Ageing the surface by sulfidation process
- 9.1.3 Steam ageing the surface
- 9.1.4 Damp-heat, steady-state ageing
- 9.2 Test method

10 Reference value using standard flux

11 Presentation of results

12 Calculation and expression of results

13 Test report

Annex A (normative) Method for the preparation of standard rosin (colophony) based liquid fluxes having 25 % (by mass) non-volatile content

- A.1 General
- A.2 Principle
- A.3 Apparatus
- A.4 Reagents
- A.5 Procedure
- A.5.1 Non-activated rosin
- A.5.2 Halogen-activated rosin
- A.6 Storage

Annex B (normative) Method for the production of test pieces with a controlled-contaminated surface for the wetting balance test (artificial sulfidation method)

- B.1 Copper test pieces for the artificial sulfidation method
- B.1.1 Reagents
- B.1.2 Apparatus
- B.1.3 Preparation of baths
- B.1.3.1 Electrolytic copper-plating bath
- B.1.3.1.1 Solution A

B.1.3.1.2 Solution B
B.1.3.1.3 Electrolysis bath
B.1.3.2 Degreasing bath
B.1.3.3 Stripping bath
B.1.3.4 Decontamination bath
B.1.4 Copper plating of blanks
B.2 Controlled contamination
B.2.1 Reagents
B.2.2 Apparatus
B.2.3 Preparation of metallic strips
B.2.4 Preparation of solutions
B.2.4.1 Preparation of solution A
B.2.4.2 Standardization of solution A
B.2.4.3 Preparation of solution B
B.2.4.4 Preparation of sulfidization bath
B.2.5 Sulfidization

Page count: 18