ISO 14920:2023-08 (E)

Thermal spraying - Spraying and fusing of self-fluxing alloys

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Influence on the substrate and design 1
4.1 Substrate 1
4.2 Design 2

5 Spray material of the self-fluxing alloy 2
5.1 Selection 2
5.2 Composition 2

6 Preparation of the component 2
6.1 General 2
6.1.1 Surface cleanliness 2
6.1.2 Removal of prior surface treatments 2
6.1.3 Pre-machining requirements 3
6.1.4 Surface preparation requirements 3
6.2 Methods of surface preparation 3
6.2.1 Surface preparation requirements 3
6.2.2 Surface preparation inspection 3
6.2.3 General masking of surface preparation 3
6.2.4 Plug masking for surface preparation 3
6.3 Cleanliness 3

7 Spray and fusion process 4
7.1 Spraying with simultaneous fusion 4
7.1.1 Procedure 4
7.1.2 Particle size and particle size range of the powder particles 4
7.1.3 Coating thickness 4
7.2 Spraying with subsequent fusion 4
7.2.1 Procedure 4
7.2.2 Particle size and particle size range of the powder particles 4
7.2.3 Coating thickness 5
7.3 Spraying technique — Procedure 5
7.3.1 General 5
7.3.2 Preheating 5
7.3.3 Spraying 5
7.3.4 Fusing the deposit 5
7.3.5 Cooling 6

8 Final machining 6

9 Hardness testing 6
9.1 General 6
9.2 Standard hardness test 6

Annex A (informative) **Reference values for the expected hardness of the fused coating** 8

Bibliography 9