

ISO 21465:2025-03 (E)

Test method for CMAS corrosion of thermal/environmental barrier coatings under dynamic thermal cycling

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Principle | | 2 |
| 5 Test methods | | 3 |
| 5.1 CMAS corrosion under dynamic thermal cycling without thermal gradient | | 3 |
| 5.1.1 CMAS composition | | 3 |
| 5.1.2 CMAS coating | | 3 |
| 5.1.3 Test method | | 3 |
| 5.1.4 Detection of the accurate temperature | | 3 |
| 5.1.5 Determination of failed samples | | 3 |
| 5.1.6 Apparatus | | 4 |
| 5.2 CMAS corrosion under dynamic thermal cycling with thermal gradient | | 4 |
| 5.2.1 CMAS suspension and CMAS precursor solution | | 4 |
| 5.2.2 CMAS concentrations | | 4 |
| 5.2.3 CMAS injection rate | | 4 |
| 5.2.4 Test method | | 4 |
| 5.2.5 Heating temperature and time | | 5 |
| 5.2.6 Determination of failed samples | | 5 |
| 5.2.7 Equipment design | | 5 |
| 6 Test report | | 6 |
| Annex A (informative) CMAS corrosion under dynamic thermal cycling without thermal gradient | | 7 |
| Bibliography | | 8 |