

DIN EN 71-8:2018-03 (E)

Safety of toys - Part 8: Activity toys for domestic use

| Contents | | Page |
|-----------------|--|-------------|
| | European foreword | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 8 |
| 4 | Requirements | 11 |
| 4.1 | General (see A.2) | 11 |
| 4.1.1 | Assembly | 11 |
| 4.1.2 | Static strength | 11 |
| 4.1.3 | Maximum height (see A.3) | 11 |
| 4.1.4 | Corners and edges (see A.4) | 11 |
| 4.1.5 | Protruding parts | 11 |
| 4.1.6 | Diameter of ropes and other means of suspension | 12 |
| 4.1.7 | Water accumulation (see A.14) | 12 |
| 4.2 | Barriers, handrails and ladders and similar means of access to activity toys | 12 |
| 4.2.1 | Barriers and handrails preventing a child from falling down (see 6.5.1, A.5) | 12 |
| 4.2.2 | Ladders and similar means of access to activity toys (see A.6) | 12 |
| 4.3 | Entrapment (see A.7) | 14 |
| 4.3.1 | Entrapment of head and neck | 14 |
| 4.3.2 | Entrapment of clothing and hair | 15 |
| 4.3.3 | Entrapment of feet | 16 |
| 4.3.4 | Entrapment of fingers | 16 |
| 4.4 | Stability of activity toys other than slides, swings and activity toys with crossbeams, and see-saws | 16 |
| 4.4.1 | General | 16 |
| 4.4.2 | Stability of activity toys with a free height of fall of 600 mm or less | 17 |
| 4.4.3 | Stability of activity toys with a free height of fall of more than 600 mm | 17 |
| 4.5 | Slides (see A.8) | 17 |
| 4.5.1 | General | 17 |
| 4.5.2 | Stability of slides | 17 |
| 4.5.3 | Retaining sides for slides (see A.9) | 17 |
| 4.5.4 | Starting, sliding and run-out sections on slides | 18 |
| 4.6 | Swings (see A.10) | 21 |
| 4.6.1 | Stability of swings and other activity toys with crossbeams | 21 |
| 4.6.2 | Static strength of crossbeams, swing devices and suspension connectors | 22 |
| 4.6.3 | Swings intended for children under 36 months | 22 |
| 4.6.4 | Minimum clearance between adjacent swing elements, and adjacent structures | 22 |
| 4.6.5 | Lateral stability of swing elements | 23 |
| 4.6.6 | Minimum clearance between swing elements and the ground (see A.11) | 24 |
| 4.6.7 | Suspension connectors and swing devices | 24 |
| 4.6.8 | Impact, geometry and design of swing elements | 25 |
| 4.7 | See-saws | 26 |
| 4.7.1 | Stability of see-saws | 26 |
| 4.7.2 | Seat/stand height | 26 |
| 4.7.3 | Restraint of motion | 26 |
| 4.7.4 | Pinching and crushing of fingers and toes | 26 |
| 4.7.5 | Hand supports | 26 |
| 4.8 | Carousels and rocking activity toys (see A.12) | 27 |
| 4.9 | Paddling pools | 27 |

| | | |
|-----------------------|---|----|
| 4.9.1 | Static strength of paddling pools with non-inflatable walls | 27 |
| 4.9.2 | Paddling pools with inflatable walls | 27 |
| 5 | Warnings, markings, and instructions | 27 |
| 5.1 | Warnings and markings | 27 |
| 5.1.1 | General | 27 |
| 5.1.2 | Paddling pools | 27 |
| 5.2 | Assembly and installation instructions | 28 |
| 5.3 | Maintenance | 29 |
| 6 | Test methods | 29 |
| 6.1 | General | 29 |
| 6.2 | Stability | 30 |
| 6.2.1 | Stability of activity toys with a free height of fall of 600 mm or less (see 4.4.2 and 4.8) | 30 |
| 6.2.2 | Stability of activity toys with a free height of fall of more than 600 mm (see 4.4.3) | 32 |
| 6.2.3 | Stability of slides (see 4.5.2) | 32 |
| 6.2.4 | Stability of swings and other activity toys with crossbeams (see 4.6.1) | 33 |
| 6.2.5 | Stability of see-saws (see 4.7.1) | 34 |
| 6.3 | Static strength | 35 |
| 6.3.1 | General | 35 |
| 6.3.2 | Strength of activity toys other than swings and paddling pools (see 4.1.2 and 4.8) | 35 |
| 6.3.3 | Strength of swings (see 4.6.2) | 37 |
| 6.4 | Dynamic strength of barriers and handrails (see 4.2.1) | 37 |
| 6.4.1 | Principle | 37 |
| 6.4.2 | Apparatus | 37 |
| 6.4.3 | Procedure | 38 |
| 6.5 | Test for head and neck entrapment (see 4.3.1) | 38 |
| 6.5.1 | Head and neck entrapment in accessible completely bound openings (see 4.2.1, 4.3.1 a) and 4.3.1 c)) | 38 |
| 6.5.2 | Head and neck entrapment in partially bound and V-shaped openings (see 4.3.1 d)) | 42 |
| 6.6 | Toggle test (see 4.3.2) | 47 |
| 6.6.1 | Principle | 47 |
| 6.6.2 | Apparatus | 47 |
| 6.6.3 | Procedure | 48 |
| 6.7 | Measurements of sliding and run-out sections on slides (see 4.5.4) | 50 |
| 6.7.1 | Measurement of inclination of the sliding section on slides (see 4.5.4 f)) | 50 |
| 6.7.2 | Measurement of the minimum angle along the sliding section and the run-out section on slides (see 4.5.4 g)) | 50 |
| 6.8 | Diameter of ropes and other means of suspension (see 4.1.6) | 51 |
| 6.9 | Determination of impact from swing elements (see 4.6.8.2) | 52 |
| 6.9.1 | Principle | 52 |
| 6.9.2 | Apparatus | 52 |
| 6.9.3 | Preparations | 54 |
| 6.9.4 | Testing | 54 |
| 6.10 | Static load test for paddling pools with non-inflatable walls (see 4.9.1) | 56 |
| 6.11 | Measurement of the height of falling protection of swings with double seats and examination of gaps between the swing seat and the falling protection | 56 |
| Annex A (informative) | Rationale | 58 |
| A.1 | Activity toys (see scope) | 58 |
| A.2 | General requirements (see 4.1) | 58 |
| A.3 | Maximum height (see 4.1.3) | 58 |
| A.4 | Corners and edges (see 4.1.4) | 58 |
| A.5 | Barriers (see 4.2) | 58 |
| A.6 | Ladders and similar means of access to activity toys (see 4.2.2) | 59 |
| A.7 | Entrapment (see 4.3) | 59 |
| A.8 | Slides (see 4.5) | 59 |
| A.9 | Retaining sides for slides (see 4.5.3) | 60 |
| A.10 | Swings (see 4.6) | 60 |
| A.11 | Clearance between swing elements and the ground for crossbeams with a maximum height of 1 200 mm (see 4.6.6) | 61 |

| | | |
|--|--|-----------|
| A.12 | Rocking activity toys and similar toys (see 4.8) | 61 |
| A.13 | Stability of swings and other activity toys with crossbeams (see 6.2.4.1.1) | 61 |
| A.14 | Drowning hazards (see 4.1.7) | 61 |
| A.15 | Warnings (see Clause 5) | 62 |
| Annex B (informative) Significant technical changes between this European Standard and the previous version | | 63 |
| Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2009/48/EC aimed to be covered | | 65 |
| Bibliography | | 66 |