DIN EN 14034-2:2011-04 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determ ination of the maximum rate of explosion pressure rise (dp/dt)<(Index)max> of dust clouds (includes Amendment A1:2011)

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Test apparatus 7
4.1 General 7
4.2 Explosion vessel 8
4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser) 10
4.4 Ignition source 13
4.5 Control unit 13
4.6 Pressure measuring system 13

5 Dust sample 13

6 Test procedure 13

7 Calibration and verification 16
7.1 Calibration 16
7.2 Verification 16

8 Safety precautions / instructions 17

9 Alternative test equipment / procedures 17

10 Test report 18

Annex A (normative) Electro Pneumatic Valve 19

Annex B (normative) Dust dispenser with 5 mm holes 22

Annex C (normative) 20 l sphere 25

C.1 General 25
C.2 Test apparatus 25
C.3 Test conditions 26
C.4 Test procedure 26
C.5 Calculation of (dp/dt)max, 20 l, Kmax and KSt 27

Annex ZA (informative) !!!!Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC""" 28

Bibliography 29

Figures Figure 1 -- 1 m³ vessel (schematic) 9

Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available) 10

Figure 3 -- Location of the 6 mm holes in the dust disperser 12

Figure 4 -- Dust dispersion and pressure-time curve 15

Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)max 16

Figure A.1 -- Electro Pneumatic Valve (schematic) 20

Figure A.2 -- Discharge characteristic of dust dispersers (without dust) 21

Figure B.1 -- Location of the 5 mm holes in the dust disperser 23

Figure B.2 -- Rebound nozzle 24

Figure B.3 -- Dispersion cup 24

Figure C.1 -- Test equipment 20 l sphere (schematic) 26

Tables Table 1 -- Maximum permissible deviations SEQ 17