

DIN EN 14034-2:2011-04 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise (dp/dt) $<(Index)max>$ of dust clouds (includes Amendment A1:2011)

Contents

	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Test apparatus	7
4.1 General	7
4.2 Explosion vessel	8
4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser)	10
4.4 Ignition source	13
4.5 Control unit	13
4.6 Pressure measuring system	13
5 Dust sample	13
6 Test procedure	13
7 Calibration and verification	16
7.1 Calibration	16
7.2 Verification	16
8 Safety precautions / instructions	17
9 Alternative test equipment / procedures	17
10 Test report	18
Annex A (normative) Electro Pneumatic Valve	19
Annex B (normative) Dust dispenser with 5 mm holes	22
Annex C (normative) 20 l sphere	25
C.1 General	25
C.2 Test apparatus	25
C.3 Test conditions	26
C.4 Test procedure	26
C.5 Calculation of $(dp/dt)_{max}$, 20 l, K _{max} and K _{St}	27
Annex ZA (informative) !!!!Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC!!!!	28
Bibliography	29

Figures	Figure 1 -- 1 m³ vessel (schematic)	9
Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available)	10	
Figure 3 -- Location of the 6 mm holes in the dust disperser	12	
Figure 4 -- Dust dispersion and pressure-time curve	15	
Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)max	16	
Figure A.1 -- Electro Pneumatic Valve (schematic)	20	
Figure A.2 -- Discharge characteristic of dust dispersers (without dust)	21	
Figure B.1 -- Location of the 5 mm holes in the dust disperser	23	
Figure B.2 -- Rebound nozzle	24	
Figure B.3 -- Dispersion cup	24	
Figure C.1 -- Test equipment 20 l sphere (schematic)	26	
Tables	Table 1 -- Maximum permissible deviations SEQ	17