

# DIN EN 14034-2:2011-04 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise  $(dp/dt)_{max}$  of dust clouds (includes Amendment A1:2011)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1 Scope .....		6
2 Normative references .....		6
3 Terms and definitions .....		6
4 Test apparatus .....		7
4.1 General .....		7
4.2 Explosion vessel .....		8
4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser) .....		10
4.4 Ignition source .....		13
4.5 Control unit .....		13
4.6 Pressure measuring system .....		13
5 Dust sample .....		13
6 Test procedure .....		13
7 Calibration and verification .....		16
7.1 Calibration .....		16
7.2 Verification .....		16
8 Safety precautions / instructions .....		17
9 Alternative test equipment / procedures .....		17
10 Test report .....		18
Annex A (normative) Electro Pneumatic Valve .....		19
Annex B (normative) Dust dispenser with 5 mm holes .....		22
Annex C (normative) 20 l sphere .....		25
C.1 General .....		25
C.2 Test apparatus .....		25
C.3 Test conditions .....		26
C.4 Test procedure .....		26
C.5 Calculation of $(dp/dt)_{max}$ , 20 l, $K_{max}$ and $K_{St}$ .....		27
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC .....		28
Bibliography .....		29

<b>Figures</b>		
<b>Figure 1</b>	<b>-- 1 m<sup>3</sup> vessel (schematic)</b>	<b>9</b>
<b>Figure 2</b>	<b>-- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available)</b>	<b>10</b>
<b>Figure 3</b>	<b>-- Location of the 6 mm holes in the dust disperser</b>	<b>12</b>
<b>Figure 4</b>	<b>-- Dust dispersion and pressure-time curve</b>	<b>15</b>
<b>Figure 5</b>	<b>-- Determination of the maximum rate of explosion pressure rise (dp/dt)<sub>max</sub></b>	<b>16</b>
<b>Figure A.1</b>	<b>-- Electro Pneumatic Valve (schematic)</b>	<b>20</b>
<b>Figure A.2</b>	<b>-- Discharge characteristic of dust dispersers (without dust)</b>	<b>21</b>
<b>Figure B.1</b>	<b>-- Location of the 5 mm holes in the dust disperser</b>	<b>23</b>
<b>Figure B.2</b>	<b>-- Rebound nozzle</b>	<b>24</b>
<b>Figure B.3</b>	<b>-- Dispersion cup</b>	<b>24</b>
<b>Figure C.1</b>	<b>-- Test equipment 20 l sphere (schematic)</b>	<b>26</b>
<b>Tables</b>		
<b>Table 1</b>	<b>-- Maximum permissible deviations SEQ</b>	<b>17</b>