ISO 17736:2010-12 (E)

Workplace air quality - Determination of isocyanate in air using a double-filter sampling device and analysis by high pressure liquid chromatography

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Principle 1

4 Reagents and materials 2

5 Apparatus 3

6 Air sampling 4
6.1 Calibration of sampling system 4
6.2 Preparation of sampling equipment 4
6.3 Preparation of MAMA-impregnated filter 4
6.4 Collection of samples 4
6.5 Blanks 5

7 Procedure 5
7.1 Safety precautions 5
7.2 Calibration standard 5

8 Sample processing 6
8.1 Vapour analysis 6
8.2 Aerosol analysis 6

9 HPLC conditions 7
9.1 General 7
9.2 HPLC conditions -- vapour isocyanates 7
9.3 HPLC conditions -- aerosol isocyanates 7

10 Analysis 8
10.1 Calibration curve 8
10.2 Quality control 8
10.3 Sample quantification 8

11 Interference 9

12 Determination of performance characteristics 10
12.1 Introduction 10
12.2 Relevant uncertainty contributions and criteria 10
12.3 Assessment of performance characteristics, following the detailed approach in ISO/IEC Guide 98-3[5] 11

Annex A (informative) Performance characteristics 18

Annex B (informative) Sample chromatograms 20

Bibliography 27