

ISO 17736:2010-12 (E)

Workplace air quality - Determination of isocyanate in air using a double-filter sampling device and analysis by high pressure liquid chromatography

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Principle	1
4	Reagents and materials	2
5	Apparatus	3
6	Air sampling	4
6.1	Calibration of sampling system	4
6.2	Preparation of sampling equipment	4
6.3	Preparation of MAMA-impregnated filter	4
6.4	Collection of samples	4
6.5	Blanks	5
7	Procedure	5
7.1	Safety precautions	5
7.2	Calibration standard	5
8	Sample processing	6
8.1	Vapour analysis	6
8.2	Aerosol analysis	6
9	HPLC conditions	7
9.1	General	7
9.2	HPLC conditions -- vapour isocyanates	7
9.3	HPLC conditions -- aerosol isocyanates	7
10	Analysis	8
10.1	Calibration curve	8
10.2	Quality control	8
10.3	Sample quantification	8
11	Interference	9
12	Determination of performance characteristics	10
12.1	Introduction	10
12.2	Relevant uncertainty contributions and criteria	10
12.3	Assessment of performance characteristics, following the detailed approach in ISO/IEC Guide 98-3[5]	11
Annex A (informative) Performance characteristics		18
Annex B (informative) Sample chromatograms		20
Bibliography		27