ISO 14382:2012-12 (E)

Workplace atmospheres - Determination of toluene diisocyanate vapours using 1-(2-pyridyl)piperazine-coated glass fibre filters and analysis by high performance liquid chromatography with ultraviolet and fluorescence detectors

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Principle 1

4 Reagents and materials 2

5 Reagent solutions 2
5.1 Preparation of TDI urea derivatives 2
5.2 Analytical standards 2
5.3 Filter extraction solution 3
5.4 1-2PP filter coating solution 3
5.5 HPLC mobile phase 3

6 Apparatus 3
6.1 Air sampler 3
6.2 Sampling pump 4
6.3 Sampling pump calibration 4
6.4 Tubing 4
6.5 Flowmeter 4
6.6 Liquid chromatography system 4

7 Air sampling 5
7.1 Calibration of sampling pump 5
7.2 Safety practices 5
7.3 Preparation of air sampler 5
7.4 Collection of air samples 5
7.5 Blanks 5
7.6 Sample shipment 5

8 HPLC analysis 6
8.1 Safety precautions 6
8.2 Sample preparation 6
8.3 Standards preparation 6
8.4 HPLC conditions 6

9 Analysis 7
9.1 Calibration 7

10 Quality control 7

11 Sample quantification 7
11.1 Determination of TDI mass per sample 7
11.2 Determination of TDI mass concentration in air 8

11.3 Determination of TDI volume fraction in air 8

12 Interferences 8

13 Determination of performance characteristics 9
13.1 Introduction 9
13.2 Relevant uncertainty contributions and criteria 10
13.3 Assessment of performance characteristics (ISO GUM approach) 10

Annex A (informative) Performance characteristics 18

Bibliography 20