

DIN EN 16232:2013-12 (E)

Child use and care articles - Infant swings

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Test equipment | 5 |
| 4.1 | Articulated test mass | 5 |
| 4.2 | Test mass A | 6 |
| 4.3 | Test mass B | 7 |
| 4.4 | Small parts cylinder | 7 |
| 4.5 | Feeler gauge | 8 |
| 4.6 | Test probes for finger entrapment | 8 |
| 4.7 | Test surface for static slippage | 9 |
| 4.8 | Test surface for stability | 9 |
| 4.9 | Test equipment for sound level measurement | 9 |
| 5 | General requirements and test conditions | 9 |
| 5.1 | Product conditioning | 9 |
| 5.2 | Test conditions | 9 |
| 5.3 | Application of forces | 10 |
| 5.4 | Tolerances | 10 |
| 5.5 | Order of tests | 10 |
| 6 | Chemical hazards - migration of certain elements | 10 |
| 7 | Thermal hazards | 11 |
| 8 | Mechanical hazards | 11 |
| 8.1 | General | 11 |
| 8.1.1 | Determination of the junction line | 11 |
| 8.1.2 | Determination of protected volume | 12 |
| 8.2 | Hazards due to sound level | 14 |
| 8.2.1 | Requirement | 14 |
| 8.2.2 | Test method | 14 |
| 8.3 | Entrapment hazards | 14 |
| 8.3.1 | Entrapment of fingers | 14 |
| 8.4 | Hazards due to falling of the child | 15 |
| 8.4.1 | Angles | 15 |
| 8.4.2 | Restraint system | 21 |
| 8.5 | Hazards due to moving parts | 22 |
| 8.5.1 | Requirements for compression points | 22 |
| 8.5.2 | Requirements for shear points | 22 |
| 8.6 | Hazards due to folding of the product | 22 |
| 8.6.1 | Requirements | 22 |
| 8.6.2 | Test methods | 23 |
| 8.7 | Hazards from entanglement in cords, ribbons and similar parts | 23 |
| 8.7.1 | Requirements | 23 |
| 8.7.2 | Test method | 23 |
| 8.8 | Choking and ingestion hazard | 23 |

| | | |
|---|--|----|
| 8.8.1 | Requirements | 23 |
| 8.8.2 | Test methods | 24 |
| 8.9 | Suffocation hazards from packaging materials | 25 |
| 8.10 | Hazards from edges, corners and protruding parts | 25 |
| 8.11 | Hazards from inadequate structural integrity | 25 |
| 8.11.1 | Static strength | 25 |
| 8.11.2 | Durability of powered swinging mechanisms | 25 |
| 8.11.3 | Reclining system | 26 |
| 8.12 | Hazards from inadequate stability | 26 |
| 8.12.1 | Requirements | 26 |
| 8.12.2 | Test method for static stability | 26 |
| 8.12.3 | Test method for dynamic stability | 27 |
| 8.13 | Hazards from possible movement of the infant swing on the floor | 27 |
| 8.13.1 | Requirement | 27 |
| 8.13.2 | Test method | 27 |
| 8.14 | Electrical hazards | 28 |
| 8.14.1 | General | 28 |
| 8.14.2 | Leakage prevention | 28 |
| 8.14.3 | Test methods | 28 |
| 9 | Product information | 29 |
| 9.1 | General | 29 |
| 9.2 | Marking of the product | 29 |
| 9.2.1 | General requirements | 29 |
| 9.2.2 | Requirements for infant swings with electrical components | 30 |
| 9.2.3 | Durability of marking | 30 |
| 9.2.4 | Test method for durability of marking | 30 |
| 9.3 | Purchase information | 30 |
| 9.4 | Instructions for use | 31 |
| 9.4.1 | General | 31 |
| 9.4.2 | Warnings | 31 |
| 9.4.3 | Additional information | 31 |
| 9.4.4 | Requirements for infant swings with electrical components | 32 |
| Annex A (informative) Rationales | | 33 |
| A.1 | General (see Clause 1) | 33 |
| A.2 | Protective volume and protective barriers (see 8.1.2 and 8.1.2.2) | 33 |
| A.3 | Hazards due to sound level (see 8.2) | 33 |
| A.4 | Hazards due to detachment of toy bars | 33 |
| A.5 | Hazards from possible movement of the infant swing on the floor (see 8.13) | 33 |
| Annex B (informative) A-deviation | | 34 |
| Bibliography | | 35 |