DIN EN 13205-2:2014-09 (E)

Workplace exposure - Assessme nt of sampler performance for measurement of airborne particle concentrations - Part 2: Laboratory performance test based on determination of sampling efficiency

Contents

Page

Foreword 4

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Symbols and abbreviations 8
4.1 Symbols 8
4.1.1 Latin 8
4.1.2 Greek 10
4.2 Enumerating subscripts 10
4.3 Abbreviations 11

5 Principle 11

6 Test method 11
6.1 General 11
6.2 Test conditions 11
6.3 Test variables 12
6.3.1 General 12
6.3.2 Particle size 14
6.3.3 Wind speed 14
6.3.4 Wind direction 14
6.3.5 Aerosol composition 14
6.3.6 Sampled or internally separated mass 14
6.3.7 Aerosol charge 14
6.3.8 Specimen variability 15
6.3.9 Excursion from the nominal flow rate 15
6.3.10 Surface treatments 15

7 Experimental requirements 15

8 Calculation of sampler bias and expanded uncertainty 17
8.1 General 17
8.2 Determination of the sampling efficiency 18
8.3 Calculation of sampler bias 18
8.3.1 Calculation of the sampled aerosol concentration 18
8.3.2 Calculation of the ideal sampled aerosol concentration 20
8.3.3 Calculation of the sampler bias 21
8.4 Calculation of the expanded uncertainty of the sampler 21
8.4.1 General 21
8.4.2 Calibration of sampler test system 22
8.4.3 Estimation of sampled concentration 23
8.4.4 Bias relative to the sampling convention 23
8.4.5 Individual sampler variability 24

8.4.6 Excursion from the nominal flow rate 24
8.4.7 Combined uncertainty (of measurement) 28
8.4.8 Expanded uncertainty 31

9 Test report 31
9.1 General 31
9.2 Testing laboratory details and sponsoring organisation 31
9.3 Description of the candidate sampler 31
9.4 Critical review of sampling process 32
9.5 Laboratory methods used 32
9.6 Details of experimental design 33
9.7 Presentation of experimental results 33
9.8 Data analysis 33
9.9 Candidate sampler performance 33
9.10 Report of workplace comparison 33
9.11 Summary and information for the user of the sampler 33

Bibliography 36