

# ISO/TR 24119:2015-11 (E)

## Safety of machinery - Evaluation of fault masking serial connection of interlocking devices associated with guards with potential free contacts

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Fault masking .....</b>	<b>5</b>
4.1	General .....	5
4.2	Direct fault masking .....	6
4.3	Unintended reset of the fault .....	6
4.4	Cable fault with unintended reset .....	7
<b>5</b>	<b>Methodology for evaluation of DC for series connected interlocking devices .....</b>	<b>8</b>
<b>6</b>	<b>Limitation of DC by effects of series connected devices .....</b>	<b>9</b>
6.1	General .....	9
6.2	Simplified method for the determination of the maximum achievable DC .....	9
6.3	Regular method for the determination of the maximum achievable DC .....	9
6.3.1	Estimation of the fault masking probability .....	9
6.3.2	Determination of the maximum achievable DC .....	10
6.4	Interlocking devices with potential free contacts and other potential free contacts of devices with different functionality connected in series .....	12
<b>7</b>	<b>Avoiding fault masking .....</b>	<b>13</b>
<b>Annex A (informative)</b>	<b>Examples of the application of the evaluation methods described in 6.2 and 6.3 .....</b>	<b>14</b>
<b>Bibliography .....</b>		<b>20</b>