

ISO 19087:2018 (E)

Workplace air — Analysis of respirable crystalline silica by Fourier-Transform Infrared spectroscopy

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative reference |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Apparatus, equipment and reagents |
| 6 | Sampling |
| 6.1 | Sample collection |
| 6.2 | Transport |
| 7 | Preparation |
| 7.1 | Preparation of calibration samples |
| 7.1.1 | Preparation of direct-on-filter calibration samples |
| 7.1.2 | Preparation of redeposition calibration samples |
| 7.1.3 | Preparation of KBr pellet calibration samples |
| 7.2 | Preparation of the collection substrate for indirect analysis |
| 7.2.1 | PVC, MCE and polycarbonate filters |
| 7.2.1.1 | Furnace treatment |
| 7.2.1.2 | Plasma ashing |
| 7.2.1.3 | Treatment with tetrahydrofuran (THF) |
| 7.2.2 | Cellulose nitrate filters |
| 7.2.3 | Polyurethane foams |
| 7.3 | Redeposition onto analysis filter |
| 7.3.1 | Crucibles from the furnace |
| 7.3.2 | Bottles or beakers from a plasma asher |
| 7.4 | Preparation of KBr pellets |
| 8 | Analytical procedure |
| 8.1 | Gravimetric analysis for respirable dust |
| 8.2 | Fourier-Transform Infrared analysis |
| 8.2.1 | Background correction |
| 8.2.2 | Measurement |
| 8.3 | Calibration |
| 9 | Evaluation of Fourier-Transform Infrared spectra |
| 9.1 | General aspects |
| 9.2 | RCS quantification using peak height |
| 9.3 | RCS quantification using peak integral |
| 9.3.1 | Determination of the absorption in the range of the analytical bands[12][14] |
| 9.3.2 | Subtraction of a reference spectrum[20] |
| 9.3.2.1 | Subtraction of a quartz or cristobalite reference spectrum |
| 9.3.3 | Other evaluation methods |
| 9.4 | Interferences |
| 10 | Calculation of results |

| | |
|---------|--|
| 10.1 | Concentration of RCS |
| 11 | Performance characteristics |
| 11.1 | Limit of detection |
| 11.2 | Limits of quantification |
| 11.3 | Uncertainty |
| 11.4 | Differences between samplers |
| 12 | Test report |
| Annex A | (normative) Sample treatment strategies for the removal of interferences |
| A.1 | Clay minerals |
| A.2 | Coal and similar carbon-based materials |
| A.3 | Removal of acid soluble components |
| A.3.1 | Calcite, gypsum, dolomite and other similar minerals |
| A.3.2 | Iron and iron compounds |
| A.4 | Removal of interferences |
| Annex B | (informative) Differences between samplers (cyclones and other types) |
| Annex C | (informative) |
| C.1 | Method that takes the influence of particle size into consideration[20] |
| C.2 | Complimentary analysis using XRD |
| Annex D | (normative) Examples of dust collection substrates and analysis filters |

Page count: 30