

ISO 21832:2018 (E)

Workplace air — Metals and metalloids in airborne particles — Requirements for evaluation of measuring procedures

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Requirements
5.1	Method description
5.1.1	Application range
5.1.2	Method performance
5.1.3	Safety information
5.1.4	Samplers
5.1.5	Sampling pumps
5.1.6	Other requirements
5.2	Performance requirements
5.2.1	Limit of quantification (LOQ)
5.2.2	Analytical recovery
5.2.3	Expanded uncertainty
6	Reagents and materials
6.1	Reagents
6.2	Standard solutions
6.3	Test materials
6.4	Reference air samples
7	Apparatus
8	Test methods
8.1	LOD and LOQ
8.1.1	Instrumental detection limit (IDL)
8.1.2	Method LOD and LOQ
8.2	Analytical recovery
8.2.1	General
8.2.2	Measuring procedures for soluble compounds of metals and metalloids
8.2.2.1	Measuring procedures that incorporate a design-based sample dissolution method
8.2.2.2	Other measuring procedures
8.2.3	Measuring procedures for total metals and metalloids that involve sample dissolution
8.2.3.1	Determination of analytical recovery using pure compounds
8.2.3.2	Determination of analytical recovery using reference materials
8.2.3.3	Determination of analytical recovery using reference air samples
8.2.3.4	Comparison of results with the acceptance criteria
8.2.4	Measuring procedures that do not involve sample dissolution
8.2.4.1	Experimental determination of analytical recovery
8.2.4.1.1	Reference air samples
8.2.4.1.2	Workplace air samples
8.2.4.1.3	Comparison of results with the acceptance criteria
8.2.4.2	Theoretical estimation of analytical recovery

8.3	Measurement uncertainty
8.3.1	Identification of random and non-random uncertainty components
8.3.2	Estimation of individual uncertainty components
8.3.2.1	General
8.3.2.2	Uncertainty associated with sampled air volume
8.3.2.3	Uncertainty associated with sampling efficiency
8.3.2.4	Uncertainty associated with sample storage and transportation
8.3.2.5	Uncertainty associated with analytical recovery
8.3.2.6	Uncertainty associated with analytical variability
8.3.3	Calculation of expanded uncertainty
9	Test report
Annex A	(informative) Guidance on determination of analytical recovery
A.1	Procedures for soluble compounds of metals and metalloids
A.2	Procedures that involve sample dissolution
A.3	Procedures that do not involve sample dissolution
Annex B	(informative) Experiments for method validation
Annex C	(informative) Estimation of uncertainty of measurement
C.1	General
C.2	Uncertainty associated with sampled air volume
C.3	Uncertainty associated with sampling efficiency
C.3.1	General
C.3.2	Uncertainty for aerosol samplers tested in accordance with the EN 13205-2 method
C.3.2.1	Principle
C.3.2.2	Sources of uncertainty for sampling efficiency
C.3.2.3	Calibration of sampler test system
C.3.2.4	Estimation of sampled aerosol concentration
C.3.2.5	Bias relative to the sampling convention
C.3.2.6	Flow excursion from the nominal flow rate (for respirable samplers and thoracic samplers)
C.3.2.7	Individual sampler variability (for respirable samplers and thoracic samplers)
C.3.3	Uncertainty for aerosol samplers tested in accordance with the EN 13205-4 method
C.3.3.1	Principle
C.3.3.2	Sources of uncertainty for sampling efficiency
C.3.3.3	Test aerosol (reference) concentration, as determined using the validated reference sampler(s)
C.3.3.4	Reference sampler
C.3.3.5	Sampler bias
C.3.3.6	Individual sampler variability (for respirable samplers and thoracic samplers)
C.3.3.7	Flow excursion from the nominal flow rate (for respirable samplers and thoracic samplers)
C.3.4	Uncertainty for aerosol samplers
C.3.4.1	Inhalable samplers
C.3.4.1.1	Experimental data
C.3.4.1.2	Estimates for general use
C.3.4.2	Respirable samplers
C.3.4.2.1	Experimental data
C.3.4.2.2	Estimates for general use
C.3.5	Efficiency of collection substrate
C.3.5.1	Filter materials
C.3.5.2	Foams
C.4	Uncertainty associated with sample storage and transportation
C.4.1	Sample storage
C.4.2	Transportation
C.5	Uncertainty associated with analytical recovery
C.5.1	General
C.5.2	Analysis of certified reference materials and/or pure compounds
C.5.3	Interlaboratory comparisons
C.5.4	Analysis of spiked collection substrates
C.5.5	Acceptable bias range
C.5.6	Procedures that incorporate a design-based sample preparation method

- C.6** **Uncertainty associated with analytical variability**
- C.6.1** **General**
- C.6.2** **Range of sample loadings at which the analytical variability has to be estimated**
- C.6.3** **Estimation using repeatability data**
- C.6.3.1** **Analytical precision**
- C.6.3.1.1** **Estimation from data obtained from the analysis of spiked collection substrates**
- C.6.3.1.2** **Estimation from data obtained by interpolation of standard deviation**
- C.6.3.1.3** **Estimation from theory**
- C.6.3.2** **Calibration standards**
- C.6.3.2.1** **Commercial stock standard solutions**
- C.6.3.2.2** **Custom-made stock standard solutions**
- C.6.3.2.3** **Reference air samples**
- C.6.3.3** **Calibration function**
- C.6.3.4** **Dilution of sample solutions (if applicable)**
- C.6.3.5** **Instrument response drift**
- C.6.4** **Estimation using laboratory reproducibility data**
- C.6.4.1** **Analytical precision**
- C.6.4.2** **Concentration of calibration standards**
- C.6.4.3** **Calibration function**
- C.6.4.4** **Dilution of the sample solutions (if applicable)**
- C.6.4.5** **Instrument response drift**
- C.6.5** **Blank subtraction**
- C.6.5.1** **General**
- C.6.5.2** **Recalculating of analytical precision to include the random uncertainty associated with blank subtraction**
- C.6.5.3** **Non-random uncertainty component associated with no blank subtraction**
- C.7** **Calculation of combined uncertainty**
- C.7.1** **Random and non-random components of sampling and analytical uncertainty**
- C.7.2** **Random and non-random uncertainty of the measuring procedure**
- C.7.3** **Combined standard uncertainty of the measuring procedure**
- C.8** **Calculation of expanded uncertainty**

Annex D (informative) Interpolation of standard deviation

Annex E (informative) Example for estimation of expanded uncertainty

Page count: 37