

# DIN EN 17199-4:2020-02 (E)

## Workplace exposure - Measurement of dustiness of bulk materials that contain or release respirable NOAA or other respirable particles - Part 4: Small rotating drum method

---

| <b>Contents</b>  | <b>Page</b> |
|--|-------------|
| European foreword.....   | 4           |
| Introduction .....   | 5           |
| 1 Scope.....   | 6           |
| 2 Normative references.....  | 6           |
| 3 Terms and definitions .....  | 7           |
| 4 Symbols and abbreviations .....  | 7           |
| 5 Principle .....  | 8           |
| 6 Equipment .....  | 10          |
| 6.1 General.....   | 10          |
| 6.2 Test apparatus.....  | 10          |
| 7 Requirements .....   | 13          |
| 7.1 General.....   | 13          |
| 7.2 Engineering control measures .....   | 14          |
| 7.3 Conditioning of the test material.....   | 14          |
| 7.4 Conditioning of the test equipment.....  | 14          |
| 8 Preparation .....  | 14          |
| 8.1 Weighing of filters.....   | 14          |
| 8.2 Test sample .....  | 14          |
| 8.3 Moisture content of the test material .....  | 15          |
| 8.4 Bulk density of the test material .....  | 15          |
| 8.5 Preparation of test apparatus .....  | 15          |
| 8.6 Aerosol instruments and aerosol samplers.....  | 15          |
| 9 Test procedure .....   | 16          |
| 9.1 General.....   | 16          |
| 9.2 Test sequence for running a dustiness test .....                                       | 17          |
| 9.3 Selection of the amount to be used for SRD dustiness triple test .....                 | 18          |
| 9.3.1 General.....   | 18          |
| 9.3.2 Selection of 6 g test material.....  | 19          |
| 9.3.3 Selection of more than 6 g test material .....                                       | 19          |
| 9.3.4 Selection of less than 6 g test material .....                                       | 20          |
| 9.4 Cleaning in between runs.....  | 20          |
| 9.5 Cleaning of equipment after conclusion of a dustiness test .....                       | 21          |
| 10 Evaluation of data .....  | 21          |
| 10.1 Respirable dustiness mass fraction.....   | 21          |
| 10.2 Use of CPC data.....  | 21          |
| 10.2.1 General.....  | 21          |
| 10.2.2 Number-based emission rate.....   | 22          |
| 10.2.3 Number-based dustiness index.....   | 22          |
| 10.2.4 Dustiness kinetics .....  | 23          |
| 10.2.5 Time needed to reach 50 % of the released number of particles during the test ..... | 23          |
| 10.3 Use of ELPI® data .....   | 23          |
| 10.3.1 General.....  | 23          |

|                              |  |           |
|------------------------------|--|-----------|
| <b>10.3.2</b>                | <b>Modal aerodynamic equivalent diameters obtained by ELPI® (aerodynamic <math>D_p</math>, <math>\mu\text{m}</math>)</b> | <b>23</b> |
| <b>10.4</b>                  | <b>Morphology and chemical characterization of the particles</b>   | <b>24</b> |
| <b>11</b>                    | <b>Test report</b>   | <b>24</b> |
| <b>Annex A (informative)</b> | <b>Example of a small rotating drum set-up</b>   | <b>26</b> |
| <b>Bibliography</b>          |  | <b>27</b> |