ISO/FDIS 17735ISO 17735:2019 (E)

Workplace atmospheres — Determination of total isocyanate groups in air using 1-(9-anthracenylmethyl)piperazine (MAP) reagent and liquid chromatographyWorkplace atmospheres — Determination of total isocyanate groups in air using 1-(9-anthracenylmethyl)piperazine (MAP) reagent and liquid chromatography

Contents

		Foreword			
		Introduction			
		Foreword			
		Introduction			
1		Scope			
_					
2		Normative references			
3	Terms and definitions				
4		Principle			
5		Reagents and materials			
	5.1	General			
	5.2	MAP reagent			
	5.3	Reagent solutions			
	5.3.1	Impinger solution			
	5.3.2	Solution for filter impregnation			
	5.3.3				
	5.3.4				
	5.4	Standard matching solutions			
	5.4.1	General			
	5.4.2				
	5.4.3	· · · · · · · · · · · · · · · · · · ·			
	5.4.4				
	5.4.5	· · · · · · · · · · · · · · · · · · ·			
	5.5	HPLC mobile phase			
	5.5.1				
	5.5.2				
	5.5.3 5.5.4	•			
_		·			
6		Apparatus			
	6.1	General			
	6.2	Sampler			
	6.2.1				
	6.2.2				
	6.2.3				
	6.3	Sampling pump			
	6.4	Tubing			
	6.5	Flowmeter Filtration and called phase extraction agreement			
	6.6 6.7	Filtration and solid-phase extraction equipment Liquid chromatographic system			
	6.7.1				
	6.7.1				
	6.7.2				
	6.7.4				
	V.1.7	TOTAL CONTROL			

	6.7.5 6.7.6	Post-column acid delivery pump Detectors				
7	Air sa	mpling				
	7.1 7.1.1 7.1.2 7.1.3 7.2 7.2.1 7.2.2 7.3 7.3.1 7.3.2 7.3.3 7.4 7.5 7.6 7.7	Pre-sampling laboratory preparation Cleaning of sampling equipment Preparation of MAP-coated filter samplers Preparation of extraction solution jars Pre-sampling field preparation Calibration of pump Preparation of samplers Collection of air samples Filter sampling Impinger sampling Sampling with an impinger followed by a filter Blanks and negative controls Bulk products Shipment of samples Filter test samples Impinger test samples				
8	HPLC	analysis				
	8.1 8.2	Instrumental settings HPLC programme				
9	Data I	handling				
	9.1 9.2	Monomer measurement Oligomer measurement (total detectable isocyanate)				
10	Calibr	ation and quality control				
11	10.1 10.2 10.3 10.4 10.5 Calcu	Standard matching solutions Calibration curves Blank tests Bulk products Quality control spikes lations Monomer				
	11.2	Oligomers (total detectable isocyanate)				
12	Interferences					
13	Deteri	mination of performance characteristics				
	13.1 13.2 13.2.1 13.2.2 13.2.2.1 13.2.2.2 13.2.2.3 13.2.2.4 13.2.2.5 13.2.3.1 13.2.3.2 13.2.3.3 13.2.3.4 13.2.3.5 13.2.3.6 13.2.3.7 13.2.3.8 13.2.3.9 13.2.3.10 13.2.3.11 13.2.3.12	Assessment of performance characteristics Collection efficiency relative to particle size distribution Air sampling Sampling volume Sampling time Variations in flow rate during sampling Conversion of sample volume to STP Combined uncertainty of sample volume Analysis Sampled mass Analyte stability Reaction/extraction efficiency Response factor Uncorrected analytical mass of compound Standard matching solutions Lack-of-fit of calibration function Drift in detector response Precision of the analysis Analytical selectivity Combined uncertainty in the analytical mass of isocyanate Combined uncertainty in the sampled mass of isocyanate				

	13.2.4	mass of compound in sample blank					
	13.2.5	Between-laboratory uncertainty contributions					
	13.2.6	Combined uncertainty					
	13.2.7	Expanded uncertainty					
	13.2.8	Uncertainty from performance criteria					
1	Sco	pe					
2	Nor	mative references					
3	Teri	ms and definitions					
4	Prir	nciple					
_	_						
5	Rea	gents and materials					
	5.1	General					
	5.2	MAP reagent					
	5.3	Reagent solutions					
	5.3.1	Impinger solution					
	5.3.2	Solution for filter impregnation					
	5.3.3	Filter extraction solution					
	5.3.4	Stability of reagent solutions					
	5.4	Standard matching solutions					
	5.4.1	General					
	5.4.2	Preparation of monomer derivatives					
	5.4.3	Preparation of standard solutions of monomer derivatives for HPLC analysis					
	5.4.4	Preparation of monomer derivatives for solid-phase extraction (SPE)					
	5.4.5	Preparation of derivative solutions of bulk isocyanate products					
	5.5	HPLC mobile phase					
	5.5.1	General					
	5.5.2	Mobile phase buffer solutions					
	5.5.3	Primary mobile phases					
	5.5.4	Post-column acid mobile phase					
	0.0.4	1 031-001dillili dold illobile pilase					
6	App	paratus					
	6.1	General					
	6.2	Sampler					
	6.2.1	General					
	6.2.2	Filters					
	6.2.3	Midget impingers					
	6.3	Sampling pump					
	6.4	Tubing					
	6.5	Flowmeter					
	6.6	Filtration and solid-phase extraction equipment					
	6.7	Liquid chromatographic system					
	6.7.1	Autosampler					
	6.7.2	Pumping system					
	6.7.3	Analytical column					
	6.7.4	Column oven					
	6.7.5	Post-column acid delivery pump					
	6.7.6	Detectors					
7	Air	sampling					
	7.1	Pre-sampling laboratory preparation					
	7.1.1	Cleaning of sampling equipment					
	7.1.2	Preparation of MAP-coated filter samplers					
	7.1.2	Preparation of extraction solution jars					
	7.1.3 7.2	Pre-sampling field preparation					
	7.2 7.2.1	Calibration of pump					
	7.2.1	Preparation of samplers					
	7.2.2	Collection of air samples					
	7.3 7.3.1	Filter sampling					
	7.3.1 7.3.2	Impinger sampling					
	7.3.2 7.3.3	Sampling with an impinger followed by a filter					
	1.3.3	SAMBINIU WILL ALL INDUNCEL TONOWEU DV A TIMEL					

	7.4 7.5	Blanks and negative controls Bulk products
	7.6	Shipment of samples
	7.7	Filter test samples
	7.8	Impinger test samples
	HPLC	analysis
8	8.1 8.2	Instrumental settings HPLC programme
	Data	handling
9	9.1 9.2	Monomer measurement Oligomer measurement (total detectable isocyanate)
10	Calib	ration and quality control
	10.1	Standard matching solutions
	10.2	Calibration curves
	10.3	Blank tests
	10.4	Bulk products
	10.5	Quality control spikes
	Calcu	ulations
1	11.1	Monomer
1	11.2	Oligomers (total detectable isocyanate)
12	Interf	erences
13		mination of performance characteristics
	13.1	General
	13.2 13.2.1	Assessment of performance characteristics Collection efficiency relative to particle size distribution
	13.2.1	Air sampling
	13.2.2.1	Sampling volume
	13.2.2.1	Sampling volume Sampling time
	13.2.2.3	Variations in flow rate during sampling
	13.2.2.4	Conversion of sample volume to STP
	13.2.2.5	Combined uncertainty of sample volume
	13.2.3	Analysis
	13.2.3.1	Sampled mass
	13.2.3.2	Analyte stability
	13.2.3.3	Reaction/extraction efficiency
	13.2.3.4	Response factor
	13.2.3.5	Uncorrected analytical mass of compound
	13.2.3.6	Standard matching solutions
	13.2.3.7	Lack-of-fit of calibration function
	13.2.3.8	Drift in detector response
	13.2.3.9	Precision of the analysis
	13.2.3.10 13.2.3.11	Analytical selectivity Combined uncertainty in the analytical mass of isocyanate
	13.2.3.11	Combined uncertainty in the analytical mass of isocyanate
	13.2.4	Mass of compound in sample blank
	13.2.5	Between-laboratory uncertainty contributions
	13.2.6	Combined uncertainty
	13.2.7	Expanded uncertainty
	13.2.8	Uncertainty from performance criteria
Anne	ex A (infor	mative) Performance characteristics
	A.1	Uncertainty estimates
	A.2	Combined uncertainty
	A.3	Expanded uncertainty
Anne	ex A (infor	mative) Performance characteristics
	A.1	Uncertainty estimates
	A.2	Combined uncertainty
	A.3	Expanded uncertainty

Page count: 0 30