

# ISO 22065:2019 (E)

## Workplace air — Gases and vapours — Requirements for evaluation of measuring procedures using pumped samplers

---

### Contents

|           |   |
|-----------|---|
|           | Foreword  |
|           | Introduction  |
| 1         | Scope   |
| 2         | Normative references  |
| 3         | Terms and definitions   |
| 4         | Symbols and abbreviated terms   |
| 5         | Sampler types   |
| 6         | Requirements  |
| 6.1       | General   |
| 6.2       | Sampler requirements  |
| 6.2.1     | Flow resistance   |
| 6.2.2     | Sampler leak test (for Type B samplers)                                   |
| 6.2.3     | Shelf life  |
| 6.2.4     | Sampler identification  |
| 6.2.5     | Marking   |
| 6.2.6     | Instructions for use  |
| 6.3       | Measuring procedure requirements  |
| 6.3.1     | Sampling procedure requirements   |
| 6.3.1.1   | General   |
| 6.3.1.2   | Sample volume   |
| 6.3.1.3   | Air flow rate   |
| 6.3.1.3.1 | Determination of the maximum air flow rate (only for impregnated filters) |
| 6.3.1.3.2 | Determination of the minimum air flow rate (only for thermal desorption)  |
| 6.3.1.4   | Storage conditions after sampling   |
| 6.3.2     | Analytical procedure requirements   |
| 6.3.2.1   | Limit of quantification   |
| 6.3.2.2   | Analytical recovery   |
| 6.3.2.3   | Blank value   |
| 6.3.3     | Expanded uncertainty  |
| 6.3.4     | Method description  |
| 6.3.4.1   | Scope of the measuring procedure  |
| 6.3.4.2   | Method performance  |
| 6.3.4.3   | Apparatus and reagents  |
| 6.3.4.4   | Safety information  |
| 7         | General test conditions   |
| 7.1       | Reagents  |
| 7.2       | Apparatus   |
| 7.3       | Calibration gas mixture   |
| 7.3.1     | Generation  |
| 7.3.2     | Determination of mass concentration                                       |
| 7.3.3     | Independent method  |
| 8         | Test methods  |
| 8.1       | General   |
| 8.2       | Sampler test methods  |

- 8.2.1 Flow resistance
- 8.2.2 Sampler leak test (for Type B samplers)
- 8.2.3 Shelf life (for Type A impregnated supports)
- 8.2.4 Sample identification
- 8.2.5 Marking
- 8.2.6 Instructions for use
- 8.3 Measuring procedure test methods
  - 8.3.1 Determination of the recommended sampling conditions
    - 8.3.1.1 Selection of sampler capacity test
    - 8.3.1.2 Sampler capacity verification test
      - 8.3.1.3 Sampler breakthrough test
        - 8.3.1.3.1 Direct method
        - 8.3.1.3.2 Chromatographic method
    - 8.3.1.4 Determination of the maximum air flow rate (only for impregnated filters)
    - 8.3.1.5 Determination of the minimum air flow rate (only for thermal desorption)
    - 8.3.1.6 Storage after sampling
      - 8.3.1.6.1 Direct method
      - 8.3.1.6.2 Sampling media spiking method
  - 8.3.2 Analytical procedure test methods
    - 8.3.2.1 Analytical limit of quantification
    - 8.3.2.2 Determination of the analytical recovery
      - 8.3.2.2.1 General
        - 8.3.2.2.2 Sampling media spiking method from the vapour phase
        - 8.3.2.2.3 Sampling media spiking method from the liquid phase
        - 8.3.2.2.4 Sampling media spiking method (for Type B samplers)
    - 8.3.2.3 Determination of the blank value
  - 8.3.3 Method recovery and method precision
    - 8.3.3.1 General
      - 8.3.3.2 Effect of the exposure concentration
      - 8.3.3.3 Effect of the relative humidity of the test atmosphere
      - 8.3.3.4 Effect of the temperature of the test atmosphere
- 8.4 Uncertainty of measurement
  - 8.4.1 Identification of random and non-random uncertainty components
  - 8.4.2 Estimation of individual uncertainty components
    - 8.4.2.1 General
      - 8.4.2.2 Uncertainty associated with sampled air volume
      - 8.4.2.3 Uncertainty associated with sample storage and transportation
      - 8.4.2.4 Uncertainty associated with method recovery
      - 8.4.2.5 Uncertainty associated with method variability
      - 8.4.2.6 Calculation of the combined standard uncertainty
  - 8.4.3 Calculation of expanded uncertainty

## 9 Test report

### Annex A (informative) Examples for the determination of the breakthrough volume

- A.1 Direct method
  - A.1.1 Apparatus
  - A.1.2 Determination
- A.2 Chromatographic method
  - A.2.1 General
    - A.2.2 Apparatus
    - A.2.3 Procedure
  - A.2.4 Corrected retention volume
  - A.2.5 Calculations

### Annex B (informative) Experiments for method validation

### Annex C (informative) Estimation of uncertainty of measurement

- C.1 General
  - C.2 Uncertainty associated with sampled air volume
    - C.2.1 Sources of uncertainty
      - C.2.2 Flow rate measurement
      - C.2.3 Pump flow stability
      - C.2.4 Sampling time

- C.3 Uncertainty associated with sampling efficiency
- C.4 Uncertainty associated with sample storage and transportation
- C.5 Uncertainty associated with method recovery
  - C.5.1 General
  - C.5.2 Analytical recovery
  - C.5.3 Method bias
  - C.5.4 Reference concentration
  - C.5.5 Effect of humidity
  - C.5.6 Effect of temperature
- C.6 Uncertainty associated with method variability
  - C.6.1 General
  - C.6.2 Method precision
  - C.6.3 Concentration of calibration solutions
  - C.6.4 Calibration function
  - C.6.5 Dilution of the sample solutions (if applicable)
  - C.6.6 Instrument response drift
  - C.6.7 Analytical precision
    - C.6.7.1 Estimation using repeatability data
    - C.6.7.2 Estimation using within laboratory reproducibility data
- C.7 Calculation of combined standard uncertainty
  - C.7.1 Random and non-random components of sampling uncertainty and analytical uncertainty
  - C.7.2 Combined standard uncertainty and expanded uncertainty

**Annex D (informative) Example for estimation of expanded uncertainty**

Page count: 38