

ISO 23506:2021 (E)

Workplace air — Analysis of airborne water immiscible mineral oil droplets and vapor with Fourier — Transform infrared spectroscopy

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Apparatus and reagents
5.1	Collecting materials for analysis and other chemicals
5.2	Sampler equipment
5.3	Analytical equipment
5.4	Other equipment
6	Polymer resin preparation
6.1	Drying
6.2	Sieving
6.3	Purification of unused polymer resin
6.3.1	General
6.3.2	Step 1: Preparatory purification with ethanol
6.3.3	Step 2: Purifying with tetrachloroethene
7	Sampling
7.1	Sampler preparation
7.1.1	Glass fibre filter (droplets)
7.1.2	Polymer resin (vapours)
7.1.3	Marking
7.1.4	Cleaning
7.1.5	Assembly
7.2	Sampling
7.2.1	Parameters
7.2.2	Pump
7.2.3	Initial flow rate
7.2.4	Flow rate verification
7.2.5	Storage and transport
8	Analysis
8.1	FTIR scanning parameters
8.2	Preparation
8.2.1	Sample
8.2.2	Solvent blank
8.2.3	Collection substrate blank
8.3	Calibration
8.3.1	General
8.3.2	Stock solution
8.3.3	Calibration standards
8.3.4	Calibration with liquid paraffin
8.4	Measurement
8.4.1	General

8.4.2	Instrument background
8.4.3	Filling the cuvette
8.4.4	Calibration
8.4.5	Sample measurement
9	Evaluation
9.1	Calibration
9.2	Samples
10	Interferences
Annex A	(informative) Validation
A.1	Assessment of the method
A.2	Recovery
A.3	Limit of quantification
A.4	Capacity of the sampler
A.4.1	General
A.4.2	Description of testing
A.5	Storage stability
A.6	Influence of the atmospheric humidity
A.7	Precision and expanded uncertainty
A.8	Calibration data of the standard mineral oil
A.9	Comparison of the different mineral oil products
Annex B	(informative) Example for estimation of expanded uncertainty

Page count: 24