

DIN EN 15051-2:2026-02 (E)

Workplace exposure - Measurement of the dustiness of bulk materials - Part 2: Rotating drum method

Contents		Page
European foreword		3
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Requirements	7
4.1	General	7
4.2	Conditioning of the bulk material	7
4.2.1	As-received condition	7
4.2.2	Conditioning specifications	8
4.3	Sample and environmental control	8
4.4	Moisture content	8
4.5	Bulk density	8
4.6	Test procedure	8
4.7	Replicate tests	8
4.8	In-house test powder	8
5	Rotating drum method	9
5.1	Description of test apparatus	9
5.2	Particle size-selective foams	12
5.3	Sampling filters	12
5.4	Ancillary equipment	13
5.5	Preparation of test sample	13
5.6	Preparation of test apparatus	13
5.7	Running the test apparatus	13
5.8	Weighing the foams and sampling filters	14
5.9	Determination of the inhalable, thoracic and respirable dustiness mass fractions	15
5.10	Limit of detection (LOD) and limit of quantification (LOQ)	16
6	Evaluation of dustiness	17
7	Test report	17
Annex A (normative) Flow rate and leak checks of the rotating drum		19
Annex B (informative) Characteristics of metal foams		20
B.1	General	20
B.2	Structure	20
B.3	Pore size	21
B.4	Chemical composition	21
B.5	Cell diameter	22
Annex C (informative) Test to identify outliers amongst values obtained from repeat tests		23
Annex D (informative) LOD and LOQ procedure for gravimetric sampling filters and foams		25
Bibliography		29