ISO/TR 13849-3:2026-03 (E)

Safety of machinery - Safety-related parts of control systems - Part 3: Markov model-based PFH calculation

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions, symbols and abbreviated terms **1**
3.1 Terms and definitions 1
3.2 Symbols and abbreviated terms 1

4 Basic assumptions **7**

5 Channels **8**
5.1 General 8
5.2 Functional channel 8
5.3 Test channel 9
5.4 Channel comprising elements connected logically in series 9
5.5 Limitation of λ_{CHD} (Capping) 10

6 Wearing parts **10**

7 Common cause failures **11**

8 Series arrangement of subsystems **12**

9 Single-channel architecture with and without test channel **13**
9.1 General 13
9.2 General solution for the single-channel architecture 13
9.3 Single-channel architecture with time-optimal testing 14
9.4 Single-channel architecture with external diagnostics 15
9.5 Single-channel architecture with external diagnostics and time-optimal testing 15
9.6 Single-channel architecture without diagnostics 15
9.7 Simplified general solution for the single-channel architecture 16
9.8 Simplified solution for the single-channel architecture with time-optimal testing 16

10 Two-channel architectures **16**
10.1 General 16
10.2 General solution for the two-channel architecture 17
10.3 Two-channel architecture with continuous testing 19
10.4 Two-channel architecture without testing 19
10.5 Simplified general solution for the two-channel architecture 20
10.6 Simplified solution for the symmetrical two-channel architecture 20
10.7 Simplified solution for the two-channel architecture with continuous testing 21
10.8 Simplified solution for the two-channel architecture without testing 21

Annex A (informative) **Examples of the application of this formula-based approach** **22**

Annex B (informative) **Derivation of the *PFH* formulas presented in the main part** **34**

Bibliography **74**