

# ISO 14119:1998-05 (E)

## Safety of machinery - Interlocking devices associated with guards - Principles for design and selection

---

<b>Contents</b>		<b>Page</b>
1	Scope .....	1
2	Normative references .....	1
3	Definitions .....	2
4	Operating principles and typical forms of interlocking devices associated with guards .....	3
5	Provisions for the design of interlocking devices (independent of the nature of the energy source) .....	9
6	Additional technological requirements for electrical interlocking devices .....	15
7	Selection of an interlocking device .....	16
Annex A Guard-operated interlocking device with one cam-operated position detector (see Introduction) .....		18
Annex B Guard-operated interlocking device with tongue-operated switch (see Introduction) .....		20
Annex C Direct (mechanical) interlocking between guard and start/stop manual control (see Introduction) .....		22
Annex D Captive-key interlocking device (see Introduction) .....		24
Annex E Trapped-key interlocking device (see Introduction) .....		26
Annex F Plug and socket interlocking device (plug/socket combination) (see Introduction) .....		28
Annex G Guard-operated interlocking device incorporating two cam-operated position detectors (see Introduction) .....		30
Annex H Mechanical interlocking between a guard and a movable element (see Introduction) .....		32
Annex J Electrical interlocking device incorporating magnetically actuated (magnetic) switches (see Introduction) .....		33
Annex K Electrical interlocking device incorporating two proximity detectors (see Introduction) .....		35
Annex L Pneumatic/hydraulic interlocking devices (see Introduction) .....		37
Annex M Interlocking device with spring-applied/power-released guard locking device .....		39
Annex N Interlocking device with guard locking, with manually operated delay device .....		41
Annex P Bibliography .....		42