ISO 8364:2017-12 (E)

Alpine skis and bindings - Binding mounting area - Requirements and test methods

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Specificationsoffreespacearea 2
4.1 Length of free space area (lz) 2
4.2 Width of the free space area (bz) 2

5 Geometrical requirements of free space area 3
5.1 Longitudinal profile of the ski surface within the free space area 3
5.2 Transverse profile of the ski surface within the free space area 3

6 Specificationsofbindingmountingarea 4
6.1 Length of binding mounting area (lb) 4
6.2 Width of binding mounting area 4
6.3 Minimum thickness of binding mounting area 4

7 Strength requirements of binding mounting area 5
7.1 Screw retention strength (Fr) 5
7.2 Stripping resistance (Fs) 5

8 Specificationsofthebinding 5
8.1 General 5
8.2 Centre-to-centre distances for binding mounting screws 5
8.2.1 Maximum centre-to-centre distance 5
8.2.2 Minimum centre-to-centre distance 6
8.3 Penetration depth of binding screws 6

9 Side walls 6

10 Marking 6
10.1 Marking of the mounting point 6
10.2 Marking of the ski properties 6

11 Apparatus 6

12 Test screws 8

13 Test methods 8
13.1 Sampling and conditioning 8
13.2 General requirements 8
13.3 Retention strength test 9
13.3.1 Mounting of the attachment plate 9
13.3.2 Positioning of the pull-out tests within the binding mounting area 10
13.3.3 Load application 11
13.4 Stripping resistance test 11

14 Test report 11

Annex A (informative) Synoptic tables 13