ISO 5355:2019 (E)

Alpine ski-boots — Requirements and test methods

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Requirements and test methods

4.1 General
4.2 Dimensions
4.2.1 Requirements
4.2.2 Testing of evenness
4.3 Design
4.3.1 Sole length
4.3.2 Symmetry
4.3.3 Side walls at boot toe
4.3.4 Side walls at boot heel
4.3.5 Free spaces
4.3.5.1 Requirements
4.3.5.2 Test methods
4.3.5.2.1 Measuring free space at boot toe
4.3.5.2.2 Measuring free space at rear of boot
4.3.6 Interfaces
4.3.6.1 Material
4.3.6.1.1 Hardness
4.3.6.1.2 Antifriction
4.3.6.1.2.1 Requirement
4.3.6.1.2.2 Test method
4.3.6.2 Front interface
4.3.6.3 Interface for the toe locking mechanism of the adjustment device
4.3.6.4 Interface for the heel locking mechanism of the adjustment device
4.3.7 Bevelled areas
4.3.8 Bearing surface at heel
4.3.8.1 Closing at the heel part
4.3.8.1.1 Requirements
4.3.8.1.2 Test method (penetration test)
4.3.8.2 Correct fit
4.3.8.2.1 Requirements
4.3.8.2.2 Test methods
4.3.8.2.2.1 Penetration test
4.3.8.2.2.2 Cylinder test
4.3.8.3 No hindrance to sideways movement
4.3.8.3.1 Requirements
4.3.8.3.2 Test methods
4.3.8.4 Proper function of ski-brakes
4.3.8.4.1 Requirements
4.3.8.4.2 Test method
4.3.8.4.2.1 Penetration test
4.3.8.4.2.2 Cylinder test
4.3.8.5 Material other than TPU
4.3.8.5.1 Requirements
4.3.8.5.2 Test method
4.3.8.6 Horseshoe-shaped bearing surfaces
4.3.9 Low-friction zone

4.3.9.1 Requirements
4.3.9.2 Test method
4.3.9.2.1 Principle
4.3.9.2.2 Test equipment and conditions
4.3.9.2.3 Procedure
4.3.10 Style of boot shell
4.3.11 Mounting point
4.3.12 Sole length

5 Marking

6 Information supplied by the manufacturer

6.1 General
6.2 User manual

Annex A (informative) Mondopoint system ski-boot sizing and marking

A.1 Reference
A.2 Range of sizes
A.3 Length intervals

Annex B (informative) Dimensions and requirements of “2nd degree”

B.1 Dimensions
B.2 Requirements

Page count: 30