

### Contents

|             |   |
|-------------|---|
|             | Foreword  |
| 1           | Scope   |
| 2           | Normative references  |
| 3           | Terms and definitions   |
| 4           | Requirements and test methods                                     |
| 4.1         | General   |
| 4.2         | Dimensions  |
| 4.2.1       | Requirements  |
| 4.2.2       | Testing of evenness   |
| 4.3         | Design  |
| 4.3.1       | Sole length   |
| 4.3.2       | Symmetry  |
| 4.3.3       | Side walls at boot toe  |
| 4.3.4       | Side walls at boot heel   |
| 4.3.5       | Free spaces   |
| 4.3.5.1     | Requirements  |
| 4.3.5.2     | Test methods  |
| 4.3.5.2.1   | Measuring free space at boot toe                                  |
| 4.3.5.2.2   | Measuring free space at rear of boot                              |
| 4.3.6       | Interfaces  |
| 4.3.6.1     | Material  |
| 4.3.6.1.1   | Hardness  |
| 4.3.6.1.2   | Antifriction  |
| 4.3.6.1.2.1 | Requirement   |
| 4.3.6.1.2.2 | Test method   |
| 4.3.6.2     | Front interface   |
| 4.3.6.3     | Interface for the toe locking mechanism of the adjustment device  |
| 4.3.6.4     | Interface for the heel locking mechanism of the adjustment device |
| 4.3.7       | Bevelled areas  |
| 4.3.8       | Bearing surface at heel   |
| 4.3.8.1     | Closing at the heel part  |
| 4.3.8.1.1   | Requirements  |
| 4.3.8.1.2   | Test method (penetration test)                                    |
| 4.3.8.2     | Correct fit   |
| 4.3.8.2.1   | Requirements  |
| 4.3.8.2.2   | Test methods  |
| 4.3.8.2.2.1 | Penetration test  |
| 4.3.8.2.2.2 | Cylinder test   |
| 4.3.8.3     | No hindrance to sideways movement                                 |
| 4.3.8.3.1   | Requirements  |
| 4.3.8.3.2   | Test methods  |
| 4.3.8.4     | Proper function of ski-brakes                                     |
| 4.3.8.4.1   | Requirements  |
| 4.3.8.4.2   | Test method   |
| 4.3.8.4.2.1 | Penetration test  |
| 4.3.8.4.2.2 | Cylinder test   |
| 4.3.8.5     | Material other than TPU   |
| 4.3.8.5.1   | Requirements  |
| 4.3.8.5.2   | Test method   |
| 4.3.8.6     | Horseshoe-shaped bearing surfaces                                 |
| 4.3.9       | Low-friction zone   |

- 4.3.9.1 Requirements
- 4.3.9.2 Test method
  - 4.3.9.2.1 Principle
  - 4.3.9.2.2 Test equipment and conditions
  - 4.3.9.2.3 Procedure
- 4.3.10 Style of boot shell
- 4.3.11 Mounting point
- 4.3.12 Sole length
- 5 Marking
- 6 Information supplied by the manufacturer
  - 6.1 General
  - 6.2 User manual
- Annex A (informative) Mondopoint system ski-boot sizing and marking
  - A.1 Reference
  - A.2 Range of sizes
  - A.3 Length intervals
- Annex B (informative) Dimensions and requirements of “2nd degree”
  - B.1 Dimensions
  - B.2 Requirements

Page count: 30