

DIN EN ISO 6185-4:2020-08 (E)

Inflatable boats - Part 4: Boats with a hull length of between 8 m and 24 m with a motor power rating of 15 kW and greater (ISO 6185-4:2011, Corrected version 2014-08-01)

| Contents | | Page |
|--|--|-------------|
| European foreword | | 4 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered | | 5 |
| Foreword | | 7 |
| Introduction | | 8 |
| 1 | Scope | 10 |
| 2 | Normative references | 10 |
| 3 | Terms and definitions | 12 |
| 4 | Symbols | 13 |
| 5 | Materials | 14 |
| 5.1 | General | 14 |
| 5.2 | Materials making up the buoyancy tube | 14 |
| 5.3 | Wood | 16 |
| 5.4 | Metal parts | 16 |
| 5.5 | Glass-reinforced plastics | 16 |
| 5.6 | Other materials | 16 |
| 5.7 | Buoyant material used in foam-filled buoyancy tubes | 16 |
| 6 | Functional components | 18 |
| 6.1 | Conditioning | 18 |
| 6.2 | Buoyancy tube and hull fittings (items bonded to the buoyancy tube) | 18 |
| 6.3 | Valves (if applicable) | 18 |
| 6.4 | Transom | 19 |
| 6.5 | Hull interior drainage | 19 |
| 6.6 | Remote steering system (where offered as standard or optional equipment) | 19 |
| 6.7 | Towing, anchoring and mooring strong points | 19 |
| 6.8 | Seating and attachment systems (where offered as standard or optional equipment) | 19 |
| 6.9 | Electrical installations (where offered as standard or optional equipment) | 20 |
| 6.10 | Engine and engine spaces | 20 |
| 6.11 | Ventilation of petrol motor and petrol tank compartments (where applicable) | 20 |
| 6.12 | Devices for lifting the boat (if applicable) | 20 |
| 6.13 | Fire protection (if applicable) | 20 |
| 6.14 | Openings in hull, deck or superstructure | 20 |
| 6.15 | Gas systems | 20 |
| 6.16 | Navigation lights | 21 |
| 6.17 | Discharge prevention | 21 |
| 6.18 | Noise emissions (applicable to inboard engines installations without integral exhaust) | 21 |
| 7 | Safety requirements of the completed boat | 21 |
| 7.1 | Maximum permissible number of persons (crew limit) | 21 |
| 7.2 | Motor power calculation | 21 |
| 7.3 | Maximal manoeuvring speed (if applicable) | 21 |
| 7.4 | Static stability of the boat | 24 |
| 7.5 | Maximum load capacity | 25 |

| | | |
|-----------|---|-----------|
| 7.6 | Buoyancy requirements | 25 |
| 7.7 | Compartmentation (inflatable buoyancy tubes) | 26 |
| 7.8 | Nominal pressures (inflatable buoyancy tubes) | 27 |
| 7.9 | Strength of the inflatable buoyancy tube | 27 |
| 7.10 | Man overboard prevention and recovery | 28 |
| 7.11 | Field of vision from the helm position | 28 |
| 7.12 | Provision for a liferaft or liferafts | 28 |
| 7.13 | Self-bailing | 28 |
| 7.14 | Buoyancy tube attachment strength test (type test only) | 29 |
| 7.15 | Strength of the rigid structure (type test only) | 31 |
| 7.16 | Strength of principal factory-fitted accessories | 31 |
| 8 | Builder's plate(s) | 32 |
| 9 | Owner's manual | 33 |
| 10 | Standard equipment | 33 |
| | Annex A (informative) Typical Type IX powered boat | 34 |
| | Annex B (informative) Typical Type X powered boat | 35 |
| | Bibliography | 36 |