

ISO 12402-7:2020 (E)

Personal flotation devices — Part 7: Materials and components — Safety requirements and test methods

Contents

| | |
|-----------|-------------------------------------|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Materials and components |
| 4.1 | General |
| 4.1.1 | Principles |
| 4.1.2 | Sampling |
| 4.1.3 | Pass or fail criteria |
| 4.1.4 | Units of measurement |
| 4.1.5 | Material |
| 4.1.5.1 | Non-metallic components and fabrics |
| 4.1.5.2 | Corrosion of metal components |
| 4.1.5.3 | Magnetic properties |
| 4.1.5.4 | Innocuousness |
| 4.1.6 | Sample conditioning |
| 4.1.6.1 | General |
| 4.1.6.2 | Standard conditioning |
| 4.1.6.3 | Temperature cycling |
| 4.1.6.4 | Accelerated weathering |
| 4.2 | Sewing thread |
| 4.2.1 | Construction |
| 4.2.2 | Performance |
| 4.2.3 | Loop breaking strength |
| 4.3 | Fabric |
| 4.3.1 | General |
| 4.3.2 | Performance |
| 4.3.3 | Colour |
| 4.4 | Structural webbing and tie tape |
| 4.4.1 | General |
| 4.4.2 | Torsional stiffness |
| 4.5 | Structural lacing |
| 4.5.1 | General |
| 4.5.2 | Construction |
| 4.5.3 | Performance |
| 4.6 | Structural zippers |
| 4.6.1 | Construction |
| 4.6.2 | Performance |
| 4.6.2.1 | General |
| 4.6.2.2 | Operability force test |
| 4.6.2.3 | Crosswise strength test |
| 4.7 | Hardware |
| 4.7.1 | Webbing closures and adjusters |
| 4.7.1.1 | Construction |
| 4.7.1.2 | Performance |
| 4.7.1.2.1 | Tensile strength |
| 4.7.1.2.2 | Strength/slippage |

- 4.7.1.2.2.1 General
- 4.7.1.2.2.2 Loop assembly method
- 4.7.1.2.2.3 Fixed straight-length method
- 4.7.1.2.3 Inadvertent release test (dual-tab closure)
- 4.7.2 Lacing closures and adjusters
 - 4.7.2.1 General
 - 4.7.2.2 Performance
 - 4.7.2.2.1 Tensile strength
 - 4.7.2.2.2 Strength/slippage
 - 4.7.2.2.2.1 General
 - 4.7.2.2.2.2 Loop assembly method
 - 4.7.2.2.2.3 Fixed straight-length method
 - 4.7.2.2.3 Tab disengagement test
 - 4.7.3 Multi-eyelet guides
 - 4.7.3.1 Construction
 - 4.7.3.2 Performance
 - 4.7.3.2.1 Tensile strength
 - 4.7.3.2.2 Cold flexibility test
- 4.8 Foam flotation material
 - 4.8.1 General
 - 4.8.2 Performance
 - 4.8.2.1 Density after water absorption
 - 4.8.2.2 Specific buoyancy
 - 4.8.2.3 Thermal stability of buoyancy material
 - 4.8.2.4 Test method for the compressibility of inherently buoyant material
 - 4.8.2.5 Buoyancy retention factor (V-factor method)
 - 4.8.2.5.1 General
 - 4.8.2.5.2 Conditioning
 - 4.8.2.5.3 Calculations
 - 4.8.2.6 Tensile strength
 - 4.8.2.7 Oil resistance
 - 4.8.2.8 Cold flexibility
 - 4.8.2.9 Compression deflection
 - 4.8.2.10 Thickness
 - 4.8.3 Knitted fabric laminated to foam flotation material
- 4.9 Inflation chamber materials
 - 4.9.1 General
 - 4.9.2 Performance
 - 4.9.2.1 Tensile strength test
 - 4.9.2.2 Trapezoid tear strength test
- 4.10 Polymeric foam coatings
 - 4.10.1 Construction
 - 4.10.2 Performance
 - 4.10.2.1 Coating adhesion
 - 4.10.2.2 Resistance to flex cracking
 - 4.10.2.3 Elongation at break
 - 4.10.2.4 Cold flexibility
 - 4.10.2.5 Blocking
 - 4.10.2.6 Water absorption
 - 4.10.2.7 Volatile loss
- 4.11 Inflation systems for hybrid and solely inflatable lifejackets
 - 4.11.1 Construction
 - 4.11.1.1 General
 - 4.11.1.2 Materials
 - 4.11.1.3 Oral inflation systems
 - 4.11.1.4 Actuation and re-arming of manual and automatic inflation systems
 - 4.11.1.5 Means for verification of mechanism operation
 - 4.11.1.6 Status indicators
 - 4.11.2 Performance
 - 4.11.2.1 General
 - 4.11.2.2 Security of protruding oral inflation valve
 - 4.11.2.3 Overpressure relief valve
 - 4.11.2.4 Use characteristics test of automatic and manual inflation systems
 - 4.11.3 Performance tests using human subjects

- 4.11.3.1 General
- 4.11.3.2 Type of inflation system and number of test participants (group size)
- 4.11.3.3 Indicator evaluation
- 4.11.4 Operability test of automatic inflation systems
- 4.11.5 Operability test of manual inflation systems
- 4.11.6 Operability test of oral systems
- 4.11.7 Discharge test of automatic and manual inflation systems
- 4.11.8 Humid atmosphere test of automatic inflation systems
- 4.11.9 System durability test of automatic and manual inflation systems
- 4.11.10 Operability test of over-pressure relief valves
- 4.11.11 Pull test of automatic and manual inflation systems, and cylinder-seal-indicating cylinders
- 4.11.12 Window material
- 4.12 Gas-filled cylinders
 - 4.12.1 Construction
 - 4.12.1.1 General
 - 4.12.1.1.1 Cylinder body
 - 4.12.1.1.2 Cap
 - 4.12.1.1.3 Gas charge
 - 4.12.1.1.4 Surface protection
 - 4.12.1.2 Materials
 - 4.12.1.2.1 Cylinder body
 - 4.12.1.2.2 Cap
 - 4.12.1.2.3 Gas
 - 4.12.1.3 Cylinder type
 - 4.12.2 Tests and acceptance criteria
 - 4.12.2.1 Pressure test
 - 4.12.2.2 Burst pressure test (hydrostatic)
 - 4.12.2.3 Rupture test (thermal)
 - 4.12.2.4 Cap piercing characteristics
 - 4.12.2.5 Leakage
 - 4.12.2.6 Mass or pressure of gas charge
 - 4.12.2.7 Cylinder volume and maximum filling
 - 4.12.2.8 Dimensions and workmanship
 - 4.12.2.9 Test methods and samples
 - 4.12.2.9.1 Test pressure test
 - 4.12.2.9.1.1 General
 - 4.12.2.9.1.2 CO₂ filled cylinders
 - 4.12.2.9.1.3 Permanent filled cylinders
 - 4.12.2.9.1.4 Test pressure test for empty cylinders
 - 4.12.2.9.1.5 Test samples for cap deformation
 - 4.12.2.9.2 Burst pressure test
 - 4.12.2.9.2.1 Procedure
 - 4.12.2.9.2.2 Test sample
 - 4.12.2.9.3 Rupture test (thermal)
 - 4.12.2.9.3.1 Procedure
 - 4.12.2.9.3.2 Test sample
 - 4.12.2.9.4 Cap piercing test
 - 4.12.2.9.4.1 Procedure
 - 4.12.2.9.4.2 Test sample
 - 4.12.2.9.5 Leakage test
 - 4.12.2.9.5.1 Procedure
 - 4.12.2.9.5.2 Test sample for determination of gas cylinder gross mass
 - 4.12.2.9.6 Test for mass of gas charge or filling pressure
 - 4.12.2.9.6.1 Procedure
 - 4.12.2.9.6.2 Test sample
 - 4.12.2.9.7 Cylinder volume and (for liquefied gases) maximum filling density test
 - 4.12.2.9.7.1 Procedure
 - 4.12.2.9.7.2 Test sample
 - 4.12.2.9.8 Dimensions and workmanship tests
 - 4.12.2.9.8.1 General
 - 4.12.2.9.8.2 Procedure
 - 4.12.2.9.8.3 Test sample
 - 4.12.2.9.9 Corrosion resistance test

- 4.12.2.9.9.1 Procedure
- 4.12.2.9.9.2 Test sample
- 4.12.3 Marking

Annex A (informative) Mildew resistance of materials: Soil burial method

- A.1 General
- A.2 Specimens
 - A.2.1 Viability control specimens
 - A.2.2 Test specimens
- A.3 Apparatus
 - A.3.1 Soil bed
 - A.3.2 Soil container
 - A.3.3 Incubator
- A.4 Procedure
- A.5 Report

Annex B (informative) Abrasion resistance of cloth: Oscillatory method (Wyzenbeek method)

- B.1 General
- B.2 Apparatus
 - B.2.1 Oscillatory cylinder
- B.3 Procedure
- B.4 Report

Annex C (informative) Example of a design drawing

Page count: 77