

ISO 23223:2021 (E)

Alpine ski boots with improved walking soles — Interface with alpine ski-bindings – Requirements and test methods

Contents

	Introduction
	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Requirements and test methods
4.1	General
4.2	Dimensions and evenness
4.2.1	Dimensions
4.2.2	Evenness
4.2.2.1	Requirement
4.2.2.2	Test method
4.3	Design
4.3.1	Sole length
4.3.2	Symmetry
4.3.3	Side walls
4.3.3.1	Boot front interface
4.3.3.2	Boot rear interface
4.3.4	Free spaces
4.3.4.1	Boot toe
4.3.4.1.1	General
4.3.4.1.2	Test method
4.3.4.2	Boot rear
4.3.4.2.1	Test method
4.3.5	Bearing surfaces
4.3.5.1	Low friction zone dimension
4.3.5.2	Hardness
4.3.5.3	Low-friction zone
4.3.5.3.1	Test method
4.3.5.3.1.1	Test equipment and conditions
4.3.5.3.1.2	Procedure
4.3.5.4	Heel bearing surface
4.3.5.4.1	General
4.3.5.4.2	Penetration test
4.3.5.4.2.1	Cylinder test
4.3.5.4.2.2	Low-friction test of the heel interface area
4.3.5.5	Toe bearing surface
4.3.5.5.1	General
4.3.5.5.2	Penetration test
4.3.5.6	Rigidity
4.3.5.6.1	General
4.3.5.6.2	Test method
4.3.6	Interfaces
4.3.6.1	Front interface
4.3.6.2	Rear interface
4.3.6.3	Hardness
4.3.6.4	Antifriction
4.3.6.4.1	General

- 4.3.6.4.2 Test method
- 4.3.6.5 Locking mechanism of the adjustment device
- 4.3.6.5.1 Toe
- 4.3.6.5.2 Heel
- 4.3.7 Style of boot shell
- 4.3.8 Mounting point
- 4.3.9 Sole length
- 5 Marking
- 6 Information supplied by the manufacturer
 - 6.1 General
 - 6.2 User manual
- Annex A (informative) Mondopoint system ski-boot sizing and marking
 - A.1 Reference
 - A.2 Range of sizes
 - A.3 Length intervals
- Annex B (informative) Dimensions and requirements of “2nd degree”
 - B.1 Dimensions
 - B.2 Requirements
- Annex C (informative) Test body for dimensional test of free space to binding
- Annex D (normative) Test gauge for dimensional check

Page count: 41