DIN EN 1177:2024-10 (E)

Impact attenuating playground surfacing - Methods of test for determination of impact attenuation (includes Amendment :2023)

Contents

Page

European foreword 4

Introduction 6

1 Scope 8

2 Normative references 8

3 Terms and definitions 8

4 Test apparatus 9
4.1 Suitability 9
4.2 Components of the apparatus 10
4.2.1 General 10
4.2.2 Headform 10
4.2.3 Signal conditioner (optional) 10
4.2.4 Guidance system 10
4.2.5 Fall height measuring equipment 11
4.2.6 Release system 11
4.2.7 Signal transmission system 11
4.2.8 Impact measuring equipment 11
4.3 Accuracy of apparatus 12
4.3.1 Calibration by a laboratory 12
4.3.2 Checks by operators 12

5 Testing procedure 13
5.1 Principle of impact measurement 13
5.1.1 General 13
5.1.2 Time/acceleration curve 13
5.1.3 Calculation of results 14
5.2 Selection and definition of test positions 14
5.3 !Testing onsite conditions 15

6 Test Method 1 - Determination of Critical Fall Height (CFH) 15
6.1 Principle 15

Table 1 -- HIC values 15
6.2 Testing in the laboratory 16
6.3 Testing on site 18

7 Test Method 2 - Determination of Impact Attenuation on site 19
7.1 Principle 19
7.2 Selection and recording of test positions 19
7.3 Carrying out the test 19
7.4 Results 20

8 Reports 20
8.1 General 20
8.2 Tests carried out in the laboratory with Method 1 20
8.3 Tests carried out on site in accordance with Method 1 21
8.4 Tests carried out on site in accordance with Method 2 22

Annex A (informative) Test rig for determination of impact attenuation 23

Figure A.1 -- Test rig for determination of critical fall height 23

Annex B (informative) Typical examples of trace of acceleration against time and curve of HIC and gmax values against drop height 24

Figure B.1 -- Typical trace of acceleration against time 24

Figure B.2 -- Example of typical curves from a test on rubber tiles for HIC and gmax values against drop height 25

Annex C (informative) Verification of computer algorithm used for the calculation of HIC (see 4.3.1.4) 26

Table C.1 -- Calculation of the output voltage for a 20 kHz frequency 26

Annex D (normative) Procedure for selection of test positions in playgrounds for Method 2 (see Clause 7) 27

D.1 Principle 27
D.2 Criteria for selection of test zones (3.12) 27

Table D.1 -- Example for test zones - Swings 28

Table D.2 -- Example for test zones - Slides and cableways 29

Table D.3 -- Example for test zones - Carousels 30

Table D.4 -- Example for test zones - Rocking equipment and spatial nets 30

Annex E (normative) Method for compaction of loose particulate impact attenuating material (see 6.2.4.5.1) 32

E.1 General 32
E.2 Measurement of layer thickness 32
E.3 Compaction procedure 32

Table E.1 -- Dimension of board sizes that can be used by different weight testers 33

Annex F (informative) Example of a regime for checking the function of an HIC test apparatus 34

Table F.1 -- Example of a regime for checking the correct function of an HIC test apparatus used weekly 34

Annex G (Informative) !History of HIC testing of impact attenuating surfaces for playgrounds and variations in test results 35