

DIN EN 1177:2024-10 (E)

Impact attenuating playground surfacing - Methods of test for determination of impact attenuation (includes Amendment :2023)

Contents		Page
European foreword		4
Introduction		6
1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Test apparatus	9
4.1	Suitability	9
4.2	Components of the apparatus	10
4.2.1	General	10
4.2.2	Headform	10
4.2.3	Signal conditioner (optional)	10
4.2.4	Guidance system	10
4.2.5	Fall height measuring equipment	11
4.2.6	Release system	11
4.2.7	Signal transmission system	11
4.2.8	Impact measuring equipment	11
4.3	Accuracy of apparatus	12
4.3.1	Calibration by a laboratory	12
4.3.2	Checks by operators	12
5	Testing procedure	13
5.1	Principle of impact measurement	13
5.1.1	General	13
5.1.2	Time/acceleration curve	13
5.1.3	Calculation of results	14
5.2	Selection and definition of test positions	14
5.3	!Testing onsite conditions	15
6	Test Method 1 - Determination of Critical Fall Height (CFH)	15
6.1	Principle	15
Table 1 -- HIC values		15
6.2	Testing in the laboratory	16
6.3	Testing on site	18
7	Test Method 2 - Determination of Impact Attenuation on site	19
7.1	Principle	19
7.2	Selection and recording of test positions	19
7.3	Carrying out the test	19
7.4	Results	20
8	Reports	20
8.1	General	20
8.2	Tests carried out in the laboratory with Method 1	20
8.3	Tests carried out on site in accordance with Method 1	21
8.4	Tests carried out on site in accordance with Method 2	22

Annex A (informative) Test rig for determination of impact attenuation	23
Figure A.1 -- Test rig for determination of critical fall height	23
Annex B (informative) Typical examples of trace of acceleration against time and curve of HIC and gmax values against drop height	24
Figure B.1 -- Typical trace of acceleration against time	24
Figure B.2 -- Example of typical curves from a test on rubber tiles for HIC and gmax values against drop height	25
Annex C (informative) Verification of computer algorithm used for the calculation of HIC (see 4.3.1.4)	26
Table C.1 -- Calculation of the output voltage for a 20 kHz frequency	26
Annex D (normative) Procedure for selection of test positions in playgrounds for Method 2 (see Clause 7)	27
D.1 Principle	27
D.2 Criteria for selection of test zones (3.12)	27
Table D.1 -- Example for test zones - Swings	28
Table D.2 -- Example for test zones - Slides and cableways	29
Table D.3 -- Example for test zones - Carousels	30
Table D.4 -- Example for test zones - Rocking equipment and spatial nets	30
Annex E (normative) Method for compaction of loose particulate impact attenuating material (see 6.2.4.5.1)	32
E.1 General	32
E.2 Measurement of layer thickness	32
E.3 Compaction procedure	32
Table E.1 -- Dimension of board sizes that can be used by different weight testers	33
Annex F (informative) Example of a regime for checking the function of an HIC test apparatus	34
Table F.1 -- Example of a regime for checking the correct function of an HIC test apparatus used weekly	34
Annex G (Informative) !History of HIC testing of impact attenuating surfaces for playgrounds and variations in test results	35