

DIN EN 17860-2:2025-06 (E)

Carrier Cycles - Part 2: Lightweight single track carrier cycles - Mechanical aspects

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 7 |
| Introduction | | 8 |
| 1 | Scope | 9 |
| 2 | Normative references | 9 |
| 3 | Terms and definitions | 10 |
| 4 | Use cases: private and commercial/professional use | 10 |
| 5 | General vehicle requirements | 10 |
| 5.1 | Numbers and condition of specimens for the strength tests | 10 |
| 5.2 | Accuracy tolerances of test conditions for brake tests and strength tests | 11 |
| 5.3 | Protrusions | 11 |
| 5.4 | Sharp edges | 11 |
| 5.5 | Securing and strength of safety-relevant fasteners | 11 |
| 5.5.1 | General | 11 |
| 5.5.2 | Minimum failure torque | 11 |
| 5.5.3 | Mechanism for folding carrier cycles | 11 |
| 5.6 | Steering function | 12 |
| 5.6.1 | General | 12 |
| 5.6.2 | Steering -- Rigidity and strength test for indirect steering systems | 12 |
| 5.6.3 | Dynamic steering fatigue test for indirect steering | 15 |
| 5.7 | Shimmy | 15 |
| 5.8 | Requirements for loading areas/load securing | 15 |
| 5.9 | Parking and stability | 16 |
| 5.9.1 | Requirement | 16 |
| 5.9.2 | Test method | 16 |
| 5.10 | Pedal clearance | 18 |
| 5.10.1 | Ground clearance | 18 |
| 5.10.2 | Toe clearance | 18 |
| 5.11 | Wheel and tyre assembly - clearance | 19 |
| 5.12 | Wheel retention | 19 |
| 5.12.1 | General | 19 |
| 5.13 | Luggage carriers | 20 |
| 5.14 | Vibrations, ergonomics and design | 20 |
| 5.14.1 | Vibrations | 20 |
| 5.14.2 | Ergonomics | 20 |
| 6 | Brakes | 20 |
| 6.1 | General | 20 |
| 6.2 | Hand-operated brakes | 20 |
| 6.2.1 | Brake lever position | 20 |
| 6.2.2 | Brake lever grip dimensions | 21 |
| 6.3 | Requirements of the test method on a test track | 23 |
| 6.4 | Requirements of the test method on a test bench | 23 |
| 6.5 | Tests | 24 |
| 6.5.1 | Test method on a test track | 24 |
| 6.5.2 | Test method on a test bench | 26 |

| | | |
|--------|--|----|
| 7 | Steering unit | 30 |
| 7.1 | Handlebar dimensions | 30 |
| 7.1.1 | General | 30 |
| 7.1.2 | Handlebar stem - Insertion-depth mark or positive stop | 31 |
| 7.1.3 | Handlebar stem to fork steerer - Clamping requirements | 31 |
| 7.2 | Handlebar grips or handlebar plugs | 31 |
| 7.2.1 | Requirements | 31 |
| 7.2.2 | Freezing test method | 32 |
| 7.2.3 | Hot water test method | 32 |
| 7.3 | Steering unit - Static strength and fastening tests | 33 |
| 7.3.1 | Steering unit - Lateral bending test | 33 |
| 7.3.2 | Handlebar stem - Forward bending test | 33 |
| 7.3.3 | Handlebar to handlebar stem -- Torsional security test | 34 |
| 7.3.4 | Bar end to handlebar - Torsional security test | 35 |
| 7.4 | Handlebar/stem unit - Dynamic test | 36 |
| 7.4.1 | General | 36 |
| 7.4.2 | Test method for stage 1 | 36 |
| 7.4.3 | Test method for stage 2 | 37 |
| 8 | Frame | 38 |
| 8.1 | Suspension frames -- Special requirements | 38 |
| 8.2 | Requirements for all frame types | 38 |
| 8.3 | Frame - Dynamic test with pedalling forces | 38 |
| 8.3.1 | General | 38 |
| 8.3.2 | Test method | 38 |
| 8.4 | Frame - Dynamic test with horizontal forces | 40 |
| 8.4.1 | General | 40 |
| 8.4.2 | Determination of the test loads | 40 |
| 8.4.3 | Test method | 41 |
| 8.5 | Frame -- Dynamic test with a vertical force onto the seat-post | 41 |
| 8.5.1 | General | 41 |
| 8.5.2 | Test method | 42 |
| 8.6 | Frame - Dynamic test with vertical forces onto the loading area | 43 |
| 8.6.1 | General | 43 |
| 8.6.2 | Test method | 43 |
| 8.7 | Frame and front fork assembly - Impact test (falling frame) | 44 |
| 8.7.1 | General | 44 |
| 8.7.2 | Requirement | 44 |
| 8.7.3 | Test method | 44 |
| 9 | Front wheel fork | 46 |
| 9.1 | General | 46 |
| 9.2 | Installation of the axle and wheel fastening | 46 |
| 9.3 | Front wheel fork --Static bending test | 46 |
| 9.3.1 | Requirements | 46 |
| 9.3.2 | Test method | 46 |
| 9.4 | Front wheel forks -- Dynamic bending test | 47 |
| 9.4.1 | General | 47 |
| 9.4.2 | Requirement | 47 |
| 9.4.3 | Test method | 47 |
| 9.5 | Front wheel fork -- Rearward impact test | 48 |
| 9.5.1 | Requirement | 48 |
| 9.5.2 | Test method 1 | 48 |
| 9.5.3 | Test method 2 | 49 |
| 9.6 | Front forks for use with hub or disc brakes | 51 |
| 9.6.1 | Requirement | 51 |
| 9.6.2 | Front fork for hub/disc brake -- Dynamic test of the brake mounting | 51 |
| 9.6.3 | Front fork for hub/disc brake - Static braking torque test | 51 |
| 10 | Wheels and wheel/tyre assembly | 52 |
| 10.1 | Wheels/tyre assembly - Concentricity tolerance and lateral tolerance | 52 |
| 10.1.1 | Requirements | 52 |

| | | |
|--------|--|----|
| 10.1.2 | Test method | 52 |
| 10.2 | Wheel/tyre assembly - Static strength test | 53 |
| 10.2.1 | Requirement | 53 |
| 10.2.2 | Test method | 53 |
| 10.3 | Wheel and wheel/tyre unit -- Dynamic test for carrier cycles | 54 |
| 10.3.1 | Requirement | 54 |
| 10.3.2 | Test method | 54 |
| 10.4 | Tyre inflation pressure | 55 |
| 10.5 | Tyre and rim compatibility | 56 |
| 10.5.1 | General | 56 |
| 10.5.2 | Wheel/ tyre assembly preparation | 56 |
| 10.5.3 | Test method | 56 |
| 11 | Front mudguard | 56 |
| 11.1 | Requirement | 56 |
| 11.2 | Front mudguard with stays test method | 56 |
| 11.2.1 | Stage 1: Test method - Tangential obstruction | 56 |
| 11.2.2 | Stage 2: Test method - Mudguard stays impact test | 57 |
| 11.2.3 | Stage 3: Test method - Radial force after impact | 58 |
| 11.3 | Front mudguard without stays test methods | 58 |
| 12 | Pedals and pedal/crank drive system | 58 |
| 12.1 | Pedal tread | 58 |
| 12.1.1 | Tread surface | 58 |
| 12.1.2 | Toe clips | 58 |
| 12.2 | Pedal - Static strength test | 59 |
| 12.2.1 | Requirement | 59 |
| 12.2.2 | Test method | 59 |
| 12.3 | Pedal - Impact test | 59 |
| 12.3.1 | Requirement | 59 |
| 12.3.2 | Test method | 59 |
| 12.4 | Pedal - Dynamic durability test | 59 |
| 12.4.1 | Requirement | 59 |
| 12.4.2 | Test method | 59 |
| 12.5 | Drive system - Static strength test | 59 |
| 12.6 | Crank assembly - Fatigue test | 60 |
| 12.6.1 | Requirement | 60 |
| 12.6.2 | Test method | 60 |
| 13 | Drive-chain and drive belt | 60 |
| 13.1 | Drive-chain | 60 |
| 13.2 | Drive belt | 60 |
| 14 | Chain-wheel and belt-drive protective device | 60 |
| 14.1 | Requirement | 60 |
| 14.2 | Chain-wheel disc and drive pulley disc diameter | 61 |
| 14.3 | Chain and drive belt protective device | 62 |
| 14.4 | Combined front gear-change guide | 63 |
| 15 | Saddles/seats and seat-posts | 64 |
| 15.1 | Limiting dimensions | 64 |
| 15.2 | Seat-post -- Insertion-depth mark or positive stop | 64 |
| 15.3 | Saddle/seat-post - Security test | 64 |
| 15.3.1 | Saddles with adjustment-clamps | 64 |
| 15.3.2 | Saddles without adjustment clamps | 65 |
| 15.4 | Saddle and saddle rail - Static strength test | 65 |
| 15.4.1 | Saddle - static strength test | 65 |
| 15.4.2 | Saddle rail (composite) - Static strength test | 65 |
| 15.4.3 | Saddle and seat-post assembly - Fatigue test | 65 |
| 15.5 | Seat-post - Strength tests | 65 |
| 15.5.1 | General | 65 |
| 15.5.2 | Test method for step 1 (dynamic test) | 65 |

| | | |
|--------|--|----|
| 15.5.3 | Test method for step 2 (static strength test) | 66 |
| 16 | Lighting systems and reflectors | 67 |
| 16.1 | General | 67 |
| 16.2 | Lighting systems | 67 |
| 16.3 | Reflectors | 67 |
| 16.4 | Rear reflectors | 67 |
| 16.4.1 | General | 67 |
| 16.4.2 | Side reflectors | 67 |
| 16.4.3 | Front reflectors | 67 |
| 16.4.4 | Pedal reflectors | 67 |
| 17 | Warning device | 68 |
| 18 | Rear-view mirror | 68 |
| 19 | Structural integrity test | 68 |
| 19.1 | General | 68 |
| 19.2 | Requirements | 68 |
| 19.3 | Verification methods | 68 |
| 20 | Marking | 69 |
| 20.1 | Requirements | 69 |
| 20.1.1 | All markings | 69 |
| 20.1.2 | Frame markings | 69 |
| 20.1.3 | Trailer coupling markings | 69 |
| 20.1.4 | Component markings | 70 |
| 20.2 | Durability test | 70 |
| 20.2.1 | Requirement | 70 |
| 20.2.2 | Test method | 70 |
| 21 | Manufacturer's instructions | 70 |
| | Annex A (informative) Vehicle configurations | 74 |
| | Annex B (informative) Reading Guide | 75 |
| | Annex C (normative) Test cycles for professional/commercial use | 77 |
| | Annex D (informative) Label | 79 |
| | Annex E (informative) Shimmy | 80 |
| | Annex F (normative) Front fork mounting device | 82 |
| | Annex G (informative) Properties of the dummy forks | 83 |
| | Annex H (informative) Calculation of the centre of gravity of cycles or carrier cycles | 85 |
| | Annex I (informative) Rationale for the necessity of a "Complete vehicle test" | 91 |
| | Annex J (informative) Rationale for the distinction between private and commercial use | 93 |
| | Bibliography | 95 |