

DIN EN 13160-5:2016-12 (E)

Leak detection systems - Part 5: Requirements and test/assessment methods for in-tank gauge systems and pressurised pipework systems

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms, definitions, symbols and abbreviated terms | 7 |
| 3.1 | Terms and definitions | 7 |
| 3.2 | Symbols and abbreviated terms | 7 |
| 4 | Requirements | 7 |
| 4.1 | Effectiveness of leak detection kits | 7 |
| 4.1.1 | General | 7 |
| 4.1.2 | Electrical or signal cable of the measuring device | 8 |
| 4.1.3 | Leak detection kit | 8 |
| 4.1.4 | Measures volumetric loss | 8 |
| 4.1.5 | Requirements for software | 9 |
| 4.1.6 | Mechanical construction | 10 |
| 4.1.7 | Effects of thermal contraction | 10 |
| 4.1.8 | Alarm device | 10 |
| 4.2 | Durability of effectiveness | 10 |
| 4.2.1 | Durability of effectiveness against temperature | 10 |
| 4.2.2 | Durability of effectiveness against chemical attack | 10 |
| 4.2.3 | Durability of effectiveness against hydraulic shock (only for measuring devices used on pressurized line) | 10 |
| 4.2.4 | Durability of effectiveness against fatigue and mechanical wear/degradation, (only for measuring devices used on pressurized line) | 10 |
| 4.2.5 | Durability of effectiveness against microbiological growth on critical surfaces involved in the measurement process | 10 |
| 5 | Testing, assessment and sampling methods | 11 |
| 5.1 | Effectiveness of leak detection kits | 11 |
| 5.1.1 | General | 11 |
| 5.1.2 | Disconnection of the electrical or signal cable of the measuring device | 11 |
| 5.1.3 | Leak detection kit | 11 |
| 5.1.4 | Measures volumetric loss | 11 |
| 5.1.5 | Software | 25 |
| 5.1.6 | Mechanical construction | 25 |
| 5.1.7 | Effects of thermal contraction | 26 |
| 5.1.8 | Alarm Device | 26 |
| 5.2 | Durability of Effectiveness | 26 |
| 5.2.1 | Durability of effectiveness against temperature | 26 |
| 5.2.2 | Durability of effectiveness against chemical attack | 26 |
| 5.2.3 | Durability of effectiveness against hydraulic shock (only for measuring devices used on pressurized line) | 28 |
| 5.2.4 | Durability of effectiveness against fatigue and mechanical wear/degradation, (only for measuring devices used on pressurized line) | 28 |
| 5.2.5 | Durability of effectiveness against microbiological growth on critical surfaces involved in the measurement process | 29 |
| 6 | Assessment and verification of constancy of performance -- AVCP | 29 |

| | | |
|---|---|----|
| 6.1 | General | 29 |
| 6.2 | Type testing | 29 |
| 6.2.1 | General | 29 |
| 6.2.2 | Test samples, testing and compliance criteria | 30 |
| 6.2.3 | Test reports | 30 |
| 6.2.4 | Shared other party results | 31 |
| 6.2.5 | Cascading determination of the product type results | 31 |
| 6.3 | Factory production control (FPC) | 32 |
| 6.3.1 | General | 32 |
| 6.3.2 | Requirements | 33 |
| 6.3.3 | Product specific requirements | 35 |
| 6.3.4 | Procedure for modifications | 36 |
| 6.3.5 | One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity | 36 |
| 7 | Marking, labelling and packaging | 37 |
| Annex A (normative) Acquisition of field data to provide a standard database for testing software leak detection systems Category A | | |
| 38 | | |
| A.1 | Objective | 38 |
| A.2 | Requirements | 39 |
| A.3 | Equipment | 40 |
| A.4 | Method | 41 |
| A.5 | Data up-loading and verification | 43 |
| A.6 | Induced leak rates - quantitative systems | 44 |
| A.7 | Induced leak rates - qualitative systems | 44 |
| A.8 | Test sequence | 44 |
| A.9 | Simulated leak test results | 45 |
| A.10 | Qualification for use | 45 |
| A.11 | Statistical analysis | 46 |
| Annex B (informative) Acquisition of field data to provide a standard database for testing software leak detection systems Category B(2) | | |
| 51 | | |
| B.1 | General | 51 |
| B.2 | File sorting and selection | 51 |
| B.3 | Data set Requirements | 51 |
| B.4 | Induced leak rates - quantitative systems | 52 |
| B.5 | Induced leak rates - qualitative systems | 52 |
| B.6 | Test sequence | 52 |
| B.7 | Evaluation of simulated leak test results | 53 |
| B.8 | Qualification for use | 53 |
| B.9 | Statistical analysis | 53 |
| B.10 | Comparison of variable and constant leak rate pairs | 56 |
| B.11 | Validation of conditions of use | 57 |
| Annex C (normative) Leak detection systems Category B(1) | | |
| 59 | | |
| C.1 | Preparation | 59 |
| C.2 | Stabilization and trial run | 59 |
| C.3 | Procedure | 59 |
| C.4 | Test results | 62 |
| C.5 | Evaluation | 63 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive Construction Products Regulation 305/2011/EU | | |
| 65 | | |
| ZA.1 | Scope and relevant characteristics | 65 |
| ZA.2 | Procedure for AVCP of leak detection systems based on volumetric loss from within the tank and/or pipework system | 66 |

ZA.2.1 System(s) of AVCP 66

ZA.2.2 Declaration of performance (DoP) 67

ZA.2.2.1 General 67

ZA.2.2.2 Content 67

ZA.2.2.3 Example of DoP 68

ZA.3 CE marking and labelling 70

Bibliography 73