

DIN EN 1765:2016-12 (E)

Rubber hose assemblies for oil suction and discharge services - Specification for the assemblies

| Contents | | Page |
|---|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Classification | 7 |
| 4.1 | General | 7 |
| 4.2 | End - use | 7 |
| 4.3 | Pressure ratings and designations | 8 |
| 5 | Materials and construction | 9 |
| 5.1 | Materials | 9 |
| 5.1.1 | Lining | 9 |
| 5.1.2 | Reinforcing plies | 9 |
| 5.1.3 | Wire helices | 9 |
| 5.1.4 | Internal and armouring wire helices | 9 |
| 5.1.5 | Cover | 9 |
| 5.2 | Construction | 9 |
| 5.2.1 | Type R: Electrically continuous | 9 |
| 5.2.2 | Type A: Electrically continuous | 10 |
| 5.2.3 | Type S: Electrically continuous or electrically discontinuous | 10 |
| 5.2.4 | Type L: Electrically continuous or electrically discontinuous | 11 |
| 6 | End connections | 12 |
| 6.1 | Nipples and flanges | 12 |
| 6.2 | Method of attachment of end connections to the hose | 12 |
| 6.3 | Electrical discontinuous assemblies | 12 |
| 6.4 | Electrical continuous assemblies with built-in nipples | 13 |
| 7 | Dimensions and tolerances | 13 |
| 7.1 | Diameters | 13 |
| 7.2 | Length | 13 |
| 8 | Physical properties | 14 |
| 8.1 | Rubber compounds | 14 |
| 8.2 | Finished hose assemblies | 14 |
| 9 | Test report | 16 |
| 10 | Type testing | 16 |
| 11 | Frequency of testing | 16 |
| 12 | Marking | 16 |
| Annex A (informative) Information to be supplied by the purchaser | | 18 |

| | |
|--|-----------|
| Annex B (informative) Recommendations for packaging and transportation of oil suction and discharge hose assemblies | 19 |
| B.1 National | 19 |
| B.2 International | 19 |
| Annex C (informative) Masses | 20 |
| Annex D (normative) Wet adhesion test | 21 |
| D.1 Scope | 21 |
| D.2 Terms and definitions | 21 |
| D.3 Principle | 21 |
| D.4 Apparatus | 21 |
| D.5 Test specimens | 21 |
| D.6 Procedure | 22 |
| D.7 Report | 22 |
| Annex E (normative) Hydrostatic test for suction and discharge hose assemblies | 23 |
| E.1 Principle | 23 |
| E.2 Apparatus | 23 |
| E.3 Test medium | 23 |
| E.4 Procedure | 23 |
| E.5 Calculation | 24 |
| E.6 Test report | 24 |
| Annex F (normative) Minimum bend radius test | 25 |
| Annex G (normative) Burst test | 27 |
| Annex H (normative) Test frequency for type testing and routine test | 28 |
| Annex I (informative) Test frequency for production acceptance tests | 29 |