

# DIN EN 16657:2018-08 (E)

## Tanks for the transport of dangerous goods - Transport tank equipment for overflow prevention devices for static tanks (includes Amendment :2018)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>5</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>3.2</b>	<b>Abbreviated terms .....</b>	<b>6</b>
<b>4</b>	<b>Requirements .....</b>	<b>6</b>
<b>4.1</b>	<b>Effectiveness .....</b>	<b>6</b>
<b>4.2</b>	<b>Construction .....</b>	<b>6</b>
<b>5</b>	<b>Overflow prevention device .....</b>	<b>6</b>
<b>5.1</b>	<b>Equipment on the tank .....</b>	<b>6</b>
<b>5.2</b>	<b>Equipment on the tank vehicle .....</b>	<b>6</b>
<b>5.3</b>	<b>EMC requirements .....</b>	<b>6</b>
<b>5.4</b>	<b>Working characteristics .....</b>	<b>7</b>
<b>5.4.1</b>	<b>General .....</b>	<b>7</b>
<b>5.4.2</b>	<b>Response time .....</b>	<b>7</b>
<b>5.4.3</b>	<b>Current interface .....</b>	<b>7</b>
<b>5.4.4</b>	<b>Operating conditions .....</b>	<b>9</b>
<b>5.4.5</b>	<b>Current interface - Auxiliary contact .....</b>	<b>10</b>
<b>5.4.6</b>	<b>Binary/Digital Interface .....</b>	<b>11</b>
<b>6</b>	<b>Test .....</b>	<b>11</b>
<b>6.1</b>	<b>Type test .....</b>	<b>11</b>
<b>6.1.1</b>	<b>General .....</b>	<b>11</b>
<b>6.1.2</b>	<b>Performance tests - controller .....</b>	<b>12</b>
<b>6.1.3</b>	<b>Fail-safe test .....</b>	<b>13</b>
<b>6.1.4</b>	<b>EMC test .....</b>	<b>13</b>
<b>6.2</b>	<b>Manufacturers production test .....</b>	<b>13</b>
<b>6.2.1</b>	<b>General .....</b>	<b>13</b>
<b>6.2.2</b>	<b>Controller response .....</b>	<b>14</b>
<b>6.2.3</b>	<b>Current interface .....</b>	<b>14</b>
<b>6.3</b>	<b>Binary/Digital interface .....</b>	<b>15</b>
<b>6.3.1</b>	<b>General .....</b>	<b>15</b>
<b>6.3.2</b>	<b>Sensor and digital interface .....</b>	<b>15</b>
<b>6.3.3</b>	<b>PRD .....</b>	<b>15</b>
<b>7</b>	<b>Marking .....</b>	<b>15</b>